# **ASTRIUM**<sup>™</sup>

# 80 mm POS thermal printer

## Ultra high-speed printer





## The latest technology for a new high-speed printer

ASTRIUM<sup>TM</sup>'s high-speed output and practical, easy-to-use features will enable you to increase speed and efficiency at your Point-of-Sales. Indeed, with a printing speed of 200 mm/s, ASTRIUM<sup>TM</sup> is a top performer in its market category. It enhances customer service at Point-of-Sales, helping to minimise lines in fast-moving retail environments.

#### High performance characteristics

ASTRIUM™ features bi-color capability, high paper roll capacity, Clamshell™ design as well as many other high performance characteristics. The high quality of ASTRIUM™'s bi-color printing enables you to highlight specific items, such as logos or advertisements. You can print your logo in a different color from the text, or make specific items of the bill stand out! Its Clamshell™ design cuts the paper roll replacement time. Just remove the spent roll and insert the new one and the printer is ready to continue working.

## A truly versatile answer to your needs

ASTRIUM™ perfectly suits any need and application thanks to its real versatility. Moreover, its compact design combined with the possibility of installing ASTRIUM™ either horizontally or vertically makes it ideal for environments where space is at premium. ASTRIUM™ offers an RS and USB interface that gives you the choice of printer connections, thanks to a flexible connection structure. ASTRIUM™ lets you change or update your operating system and switch from an RS or USB port without changing the system. This flexibility is due to an interchangeable interface module that can be easily replaced by any operator.



Ш

(0205

**™MUMTS** 







### 80 mm POS thermal printer

#### Characteristics

#### mm/s $\mathsf{mm}$

200 (single color)

70 (two colors)

UPC-A, UPC-E, JAN8&13, ITF, Code 39/93/128, Codabar

Two color print capability Resolution **Number of dots** Columns

Printing speed (max)

**Printing width** 

dot/mm dot column

576 42/56 (80 mm)

ASTRIUM™

Character size Default code page 32/42 (60 mm) 30/40 (58 mm)

YES

8

Bar code type

dot\*dot 10\*19, 13\*27

Paper width

CP210/437/850/852/857/858/860/862/863/864/865/866 WPC 1251/1253/1254/1255/1257/255

mm 58 & 60 mm with optional paper guide mm 100

Paper roll diameter Paper loading Operating voltage Power consumption Head pulse life Mechanical reliability

Clamshell™ ٧ 24 Α 2.5 0.5\*10<sup>8</sup> pulse 100 km

Dimensions (W\*D\*H) **Operating temperature Operating humidity** Cutter

140\*217\*157 mm °C/°F 0 to 40/32 to 104 %RH 20 to 85

**Cutter life Data buffer** Flash memory extension

Auto cutter (partial cuts) and tear bar cuts 1 Million

**RAM** memory extension Interface

**Kbytes** Kbytes 384 Bytes Up to 1 MB - 4MB extension available upon request RS232 (DB9 or DB25), USB, Parallel, Ethernet

**Emulation** 

**Driver** 

**Options** 

Windows™ 98/98SE/ME/00/NT/XP - OPOS ESC/POS™

**CEM & Safety standards Added features** 

FCC Class A, CE Class B, UL, cUL 60950, C-Tick Buzzer, 2 CDKO, Casing colors: light/dark gray

Wall mounting kit, paper guide.

Interchangeable interfaces: RS232, USB, Parallel, Ethernet Extended memory for back-up journal (fiscal capability)

#### Other Axiohm's products



#### Thermal Printer Mechanisms

Axiohm's thermal printer mechanisms meet the most demanding market needs in terms of printing speed (up to 250 mm/s), paper width (60 mm, 2\*38 mm, 80 mm & 82.5 mm), ruggedness, compactness, both easy integration and use.



#### Turnkey Printing Selutions

AXIOHM's kiosk printers are designed primarily for installation in public access terminals, but can be used in almost any transaction printing application that requires an easy-tointegrate "plug & play" product.



#### Centreller Beards

Axiohm offers an extensive range of controller boards with embedded firmware to manage its full line of thermal printer mechanisms. The controller boards' features have been designed to meet your needs in terms of functionality and competitiveness.

# -Axiohm

France (for EMEA & Asia/Pacific) 1, rue d'Arcueil - BP 820 92542 Montrouge Cedex - FRANCE Tel: +33 1 58 07 17 17 Fax: +33 1 58 07 17 18 info@axiohm.com

455 Wards Corner Road Suite 500 Loveland, OH 45140 - USA Tel: +1 (513) 248-9900 Fax: +1 (513) 248-8274 namsales@axiohm.com