



BLUE WING KEYFOB READ WRITE HITAG 1

Description:	BLUE WING KEYFOB Hitag 1		
IC type:	Hitag 1 2048 bit Read Write		
IC on request:	(R/O 125kHz EM4100 Unique) (R/W 125 kHz: 5557, Hitag 2, S Titan EM4450)	(R/W 13.56 MHz: I-CODE SLI SL2, Mifare 1K)	
Physical:	Dimensions:	56.2 mm x 31.5 mm	± 0.2 mm
	Thickness:	8.5 mm	± 0.2 mm
	Hole Ø:	5,0 mm	± 0.2 mm
	Weight:	7.2 g	± 0.2 g
	Material:	Polycarbonate	Transparent Blue (Transparent Red on request)
	Assembly:	Ultrasonic Welded	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz (At room temperature 20°C)
Thermal:	Operating Temperature:	-30°C to +65°C	
	Storage Temperature:	-35°C to +85°C	
Protection Class:	IP66 (20°C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Laser engraving of UID code, customised logos are available upon request.		
Part number:	TAN-04-AA		

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.