

DUO CARD MIFARE 1K + UNIQUE



Description:	Configurable Duo card MIFARE with 1Kbytes read-write memory bits and additional with separated 125 kHz UNIQUE 64 bit read-only memory		
IC type:	MIFARE S50, EM4100 (optional other LF chip like 5557, Hitag 1, 2, S available instead of EM4100 on request)		
Mifare-Transport keys:	KEY A : FF FF FF FF FF FF	KEY B : no fixed code, variable	
Physical:	Thickness:	00.82 mm	
	Length:	85,6 mm	
	Width:	54 mm	
	Weight:	06.5 g	± 0.50 g
	Material:	PVC	White / white
Electrical:	Operating Frequencies:	13.56 MHz, 125 kHz	
Dual Frequency:	The Dual Frequency Card is a single card with two different operating frequency technologies. These two contactless transponders are not connected and do not interact with each other.		
Thermal:	Operating temperature: -25°C up to +55°C		
ISO:	ISO7816	ISO14443A	
Surface:	Matte or Gloss. The card is based on COB module technology. The printer parameters have to be adjusted to ensure correct printing.		
Magnetic stripe:	HICO 2750 Oe magnetic stripe is available at ISO position Optional different HICO and LOCO magnetic stripes are available		
Specials:	Different chip code printing, customised logos, colour printing are available upon request		
Part number:	TAA-22-AA	w/o magnetic stripe	
	TAB-22-AA	with 2750 Oe magnetic stripe	

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.