



EPOXY DISC TAG 30 MM UNIQUE

Description:	EPOXY DISC TAG 30mm Unique		
IC type:	EM H410x 64 bits RF/64 ASK Manchester		
Physical:	Diameter:	30.00 mm	± 0.50 mm
	Thickness:	01.00 mm	± 0.20 mm
	Hole:	03.20 mm	± 0.10 mm
	Weight:	02.00 g	± 0.50 g
	Material:	Ероху	Black
Electrical:	Operating Frequency:	125 kHz	± 6 kHz
Thermal:	Storage temperatures:	-40°C up to 90°C	
	Operating temperatures:	-25°C up to 70°C	
Chemical:	Water immersion IP66		
Mechanical:	Axial compression	800N	10s
	Radial compression	400N	10s
	Vibration	IEC 68.2.6	10g,102000Hz, 3 axis, 2.5h
	Shock	IEC68.2.27	40g, 18 ms, 6 axis, 2000 times
Special:	Upon request other chip technologies are available.		
Part number:	TBC-00-AA		

[©] TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.