



EPOXY KEY FOB UNIQUE

Description:	EPOXY KEY FOB Unique		
IC type:	EM4100 64 bit Read Only ASK Manchester		
IC on request:	(R/W 125 kHz: 5557, Hitag 1, 2, S)	(R/W 13.56 MHz: I-CODE SLI SL2, Mifare)	Other Type-Part-No's. see below.
Physical:	Dimensions:	45 mm x 30 mm	± 0.5 mm
	Thickness:	1.89 mm	± 0.5 mm
	Hole:	4 mm	± 0.5 mm
	Weight:	4 g	± 0.4 g
	Material:	EPOXY + GF	Standard Colour: Black
	Assembly:	Laminated	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz (At room temperature 20 °C)
Thermal:	Operating Temperature:	-20 °C to +75 °C	
	Storage Temperature:	-30 °C to + 100 °C	
Protection Class:	IP66 (20 °C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions. With TECTUS Reader 100 mm up to 300 mm. (At room temperature 20 °C)		
Type: Part-No.	EM4100 Unique: TCP-00-AA	5557/5567: TCP-02-AA	Hitag 1: / 2 : TCP-04-AA /05-AA
Type: Part-No.	MIFARE 1K (S50): : TCP-06-AA	I-Code SLI SL2: TCP-15-AA	Hitag S 2048: TCP-13-AA