

Obv!os® Gladius

POS Terminal

Obv!os® presents the next generation of integrated systems designed specifically for POS.

The Gladius series is a powerful and battle-hardened range of POS terminals that are the Obv!os® weapon of choice for any transaction environment.

Visit our website for more information
www.obvios.com.au



Obv!os®



PRODUCT DESCRIPTION

The Gladius series are compact and powerful integrated POS terminals that are arguably the most robust and flexible in their class.

Gladius terminals are housed in an elegant, die-cast aluminium case, which, in addition to creating a solution designed to withstand the harshest operating environments, acts as a heat sink allowing the internal electronics to operate at the lowest possible temperatures.

Gladius terminals are equipped as standard, with 512MB RAM, hard disk drive and sufficient I/O ports to control the complete requirement of peripherals including power for a thermal receipt printer, cash drawer and barcode scanner.

APPLICATIONS

POINT OF SALE

GAMING

RETAIL

HOSPITALITY

MANUFACTURING

H700 SERIES SPECIFICATIONS

Construction	Die-cast Aluminium Casing
Display	12.1" 800x600 TFT colour display 15.1" 1024x768 TFT colour display
Touch Panel	ELO 5-wire resistive touch screen
CPU	Via C3 1.0Ghz, Intel PIII 1.2G, Intel PIV 2.0G
RAM	512MB DRAM
Solid State Disk	Compact Flash (Optional)
LAN	10/100BaseT Ethernet
Serial Ports	Four RS-232C serial ports COM1/2 RS-232C in 9-pin D-sub male (Pin 9 may set to supply +5V or +12V) COM2 may be set as RS-422/RS-485 COM3 used for touch screen panel COM4 (RJ-45) used for customer display
Parallel Ports	One Parallel port support SPP/EPP/ECP modes. 25-pin D-sub female
VGA Port	One connector for external VGA monitor
Sound Port	Line out for powered speakers (12.1" screen), internal speakers (15.1" screen)
USB Port	Two USB ports
Keyboard Port	PS/2 style keyboard port
Mouse Port	PS/2 style mouse port
CD-ROM Port	One connector for external CD-ROM drive
Cash Drawer Port	One RJ-11 cash drawer port capable of driving two +12V drawers
Power Supply	External 250W power adapter with +24V DC output
Power Consumption	-40 to 50W
Height	310mm with display upright
Width	315mm, 360mm with MCR
Base Depth	265mm
Base Width	245mm
Display Height	245mm
Display Tilt	90° (upright) to 180° (flat)
Operating Temp.	5°C to 40°C
Compliance	CE, Class-B, TUV, FCC, UL, CSA, CTick
Operating Systems	DOS, Windows 98, NT, 2000, XP, WinCE, Linux (RedHat 7.3)

OPTIONS

Rear 12.1" TFT colour display
Rear customer display (2x20 line)
Magnetic card or smart card reader
I-button
External CD-ROM
External USB floppy disk drive
Internal 3.5" hard disk drive
ELO IR Carroll Touch Upgrade
Wireless 802.11b

Distributed by DH Technology

SYDNEY

Level 3, 39 Leighton Place
Hornsby NSW 2077
Tel: 02 9477 1999
Fax: 02 9477 1453

MELBOURNE

337 Warrigal Road
Cheltenham VIC 3192
Tel: 03 8585 1087
Fax: 03 9585 3876

ADELAIDE

106B Rundle Street
Kent Town SA 5067
Tel: 08 8362 0007
Fax: 08 8363 3854

Obv!os® is a registered trademark of DH Technology

Internet: www.dhtechnology.com.au

ABN: 65 003 608 580

