

Obv!os® Glaive

POS Terminal

Obv!os® presents the Glaive series, a range of POS terminals that set a new benchmark in the world of purpose built retail hardware.

The Glaive is the first terminal of its type to successfully offer a stand-alone or client server configuration, at a price point that will convert many to its sleek and practical design.

Visit our website for more information
www.obvios.com





PRODUCT DESCRIPTION

Continuing in the tradition of the Obvios range, the Glaive is encased in die-cast aluminium and offers the robust and durable quality you have come to expect from this market leading brand.

The Glaive is a fanless terminal capable of running the latest embedded operating systems.

Available with a Celeron processor, the Glaive performs equally well with disk-based OS applications, or the embedded environment of WinCE, XP and Linux. With native wireless support and a range of screen configurations, Glaive is your first choice for state-of-the-art terminal performance.

APPLICATIONS

POINT OF SALE

EFTPOS

RETAIL

HOSPITALITY

MANUFACTURING

HOME AUTOMATION

ACCESS CONTROL

RT560 SERIES SPECIFICATIONS

Construction	Die-cast Aluminium Casing
Display	12.1" 800x600 TFT colour display 15.1" 1024x768 TFT colour display
Touch Panel	ELO 5-wire resistive touch screen
CPU	Celeron M (650 MHz)*
RAM	256MB SD RAM
Solid State Disk	Compact Flash (Optional)
LAN	10/100 BaseT Ethernet
Serial Ports	Three RS-232C serial ports COM1 /2 RS-232C in 9-pin D-sub male (Pin 9 may set to supply +5V or +12V) COM2 may be set as RS-422/RS-485 COM4 (RJ-45)
VGA Port	One connector for external VGA monitor
Sound Port	Line out for powered speakers
USB Port	Three USB ports
Keyboard Port	PS/2 style keyboard port
Cash Drawer Port	One RJ-11 cash drawer port capable of driving two +12V drawers
Power Supply	External 60W power adapter with +24V DC output
Power Consumption	~40 to 50W
Dimensions	320 (W) x 235 (L) x 320(H) mm (12.1") 365 (W) x 235 (L) x 360 (H) mm (15")
Display Tilt	90° (upright) to 180° (flat)
Operating Temp.	5°C to 40°C
Compliance	CE, Class-B, TUV, FCC, UL, CSA, CTick
Operating Systems	DOS, Windows 98, NT, 2000, XP, WinCE, Linux (RedHat 7.3), XP Embedded

OPTIONS

Magnetic Card Reader (MCR)
Customer Vacuum Fluorescent Display (VFD)
32-key Keypad with I-button and MCR
Wireless 802.11b

* Specifications subject to change without notice.

Distributed by Obvios Ltd

USA

Suite 110, 2120 North Central
Phoenix, AZ 85004, USA
UNITED STATES OF AMERICA
Tel: +1 866 4 628 467
Email: sales@obvios.com

EUROPE

2 Station Approach
Bicester, Oxfordshire OX26 6BZ
UNITED KINGDOM
Tel: +44 1869 365 400
Email: sales@obvios.com

ASIA PACIFIC

Level 3, 39 Leighton Place
Hornsby, NSW 2077
AUSTRALIA
Tel: +61 2 9472 7100
Email: sales@obvios.com

Obvios® is a registered trademark

Internet: www.obvios.com

© Copyright 2006 Obvios Ltd

