

ISO CARD UNIQUE OVERLAY



Description:	Proximity ISO card Unique with transparent overlay		
IC type:	EM H410x 64 bits RF/64 ASK Manchester		
Physical:	Thickness:	00.76 mm	± 0.08 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Weight:	05.60 g	± 0.50 g
	Material:	PVC	White / white
Electrical:	Operating Frequency:	125 kHz	± 6 kHz
Thermal:	Operating temperatures:	-35°C up to +50°C	
ISO:	7816		
Surface:	Thanks to the overlays the cards can be printed with higher quality and the cards are scratches resistant. The printer parameters have to be adjusted to ensure correct printing		
Magnetic stripe:	HICO 2750 Oe magnetic stripe is available at ISO position Optional different HICO and LOCO magnetic stripes are available		
Contact Module:	Upon request a contact module can be embed at ISO position		
Punch slots:	Upon request 2 slots can be punched (1 on the short edge and 1 on the long edge)		
Specials:	Different chip code printing, customised logos, colour printing are available upon request		
Part number:	TAA-00-AD	W/O magnetic stripe	
	TAB-00-AD	2750 Oe magnetic stripe	