



ISO CARD WHITE

Description:	Proximity ISO card White			
IC type:	EM H410x 64 bits and 5555 (Q5)			
Physical:	Thickness:	00.76 mm	± 0.08 mm	
	Length:	85.60 mm	± 0.12 mm	
	Width:	53.98 mm	± 0.05 mm	
	Weight:	05.60 g	± 0.50 g	
	Material:	PVC	White / white	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz	
Thermal:	Operating temperatures:	-35°C up to +50°C		
ISO:	ISO 7816 / the cards are perfectly working and are ISO qualified			
Surface:	Cards have small visual defects. We give no guaranty on the printability			
		,		
Magnetic stripe:	Upon request HICO 2750 Oe magnetic stripe is available at ISO position Optional different HICO and LOCO magnetic stripes are available			
Contact Module:	Customer may embed a contact module at ISO position. Upon request an identification mark can be added to show the card free areas			
Punch slots:	3 different punch slot positions are available			
Part number:	TAM-00-AA	Unique W/O magnetic stripe	Unique W/O magnetic stripe	
	TAS-00-AA	Unique 2750 Oe magnetic s	Unique 2750 Oe magnetic stripe (upon request)	
	TAM-01-AA	5555 (Q5) W/O magnetic st	5555 (Q5) W/O magnetic stripe	
	TAS-01-AA	5555 (Q5) 2750 Oe magnet	5555 (Q5) 2750 Oe magnetic stripe (upon request)	

[©] TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.