



ISO CARD UNIQUE

Description:	Proximity ISO card Unique			
IC type:	EM H410x 64 bits RF/64 ASK Manchester			
Physical:	Thickness:	00.76 mm	± 0.08 mm	
	Length:	85.60 mm	± 0.12 mm	
	Width:	53.98 mm	± 0.05 mm	
	Weight:	05.60 g	± 0.50 g	
	Material:	PVC	White / white	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz	
Thermal:	Operating temperatures:	-35°C up to +50°C		
ISO:	7816			
Surface:	The card is based on module technology. The printer parameters have to be adjusted to ensure correct printing			
Magnetic stripe:	HICO 2750 Oe magnetic stripe is available at ISO position Optional different HICO and LOCO magnetic stripes are available			
Contact Module:	Upon request a contact module can be embed at ISO position			
Punch slots:	Upon request 2 slots can be punched (1 on the short edge and 1 on the long edge)			
Specials:	Different chip code printing, customised logos, colour printing are available upon request			
Part number:	TAA-00-AA	W/O magnetic stripe	W/O magnetic stripe	
	TAB-00-AA	2750 Oe magnetic stripe		

[©] TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.