



KettleTag®PLUS

Tags for Fabricators and Galvanizers

	KettleTag®PLUS
<i>Industry</i>	Metal galvanizing
<i>Typical Customer</i>	Galvanizers; Fabricators
<i>Purpose</i>	Tracking work-pieces through the entire galvanizing process
<i>Resistance</i>	
<i>Heat</i>	1000°F (538°C) after removal of protective laminate
<i>Chemical</i>	Tags legible after most caustic/acid rinses (10 minutes each) and molten zinc bath
<i>Abrasion</i>	Moderate
<i>Ultraviolet</i>	Highly resistant to sunlight and fading
<i>Sizes</i>	<i>Width:</i> 3.0 in (76 mm) <i>Lengths:</i> to customer specification, not less than 1.0 in (25 mm) <i>Typical Lengths:</i> 3.0 in (76 mm)
<i>Composition</i>	Metal, with high contrast laser-markable coatings and specialty laminates
<i>Available for PrePrint</i>	Yes
<i>Available Colors</i>	White, colors by special order



Readable Before

...and Readable After

The Only Galvanizing Tags with Text and Barcodes that Survive The Entire Galvanizing Process

The American Galvanizer's Association lists 9 steps in the hot dip galvanizing process. Since 2001, our KettleTagPLUS has been surviving them all.

Attach one tag and you're done. KettleTagPLUS means you don't have to remove your metal tags before the acid dip, or remove your paper tags before the molten zinc bath. No removing; no reattaching.

- ⊕ Increased efficiency for galvanizers.
- ⊕ Traceability and error-proof installations for fabricators.
- ⊕ Eliminates unsafe handling.
- ⊕ Processes vary. Call for samples and test KettleTagPLUS in your process.



Printers & Tags that Cut Costs, Increase Safety and Assure Traceability