



Description:	LENS TAG 170 I-CODE SLI SL2		
IC type:	I-Code SLI SL2 ICS20 1024 bits ISO 15693, ISO18000		
	Anticollision acc. ISO 15693		
Physical:	Diameter:	17.0 mm	± 0.2 mm
	Thickness:	3.0 mm	± 0.2 mm
	Hole:	none	
	Weight:	1.0 g	± 0.5 g
	Material:	Nylon + GF	Black
	Assembly	Injection Molding	
Electrical:	Operating Frequency:	13.56 MHz	
Thermal:	Operating Temperature:	-25℃ to +85℃	
	Storage Temperature: -30 °C to 130 °C (1 x 500 h), -30 °C to 150 °C (1x 24 h)		
Protection Class:	IP68 (20℃, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Laser engraving of UID code, customised logos are available upon request.		
Part number:	TAZ-15-AA		

[®] TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.