



LENS TAG 220 ISO15693 2K BIT Read Write

Description:	LENS TAG 220 ISO15693 2 K bits Read Write		
IC type:	Read Write 2048 bits, 64 bits UID, ISO 15693-2,-3, ISO18000		
Anticollision:	Up to 50 TAGs per second	(reader / antenna dependent)	
Physical:	Diameter:	22.0 mm	± 0.2 mm
	Thickness:	3.0 mm	± 0.2 mm
	Hole:	none	
	Weight:	1.6 g	± 0.3 g
	Material:	PPS	Black
	Assembly	Injection Molding	
Electrical:	Operating Frequency:	13,56 MHz	± 300 kHz (At room temperature 20 °C)
Thermal:	Operating Temperature:	-25 °C to +90 °C	
	Storage Temperature: -20 °C to 120 °C, +160 °C (1 x 50 h), +220 °C (1 x 30 seconds)		
Protection Class:	IP68	Chemical Resistance: Typical chemicals used in laundry and dry cleaning	
Vibration:	ISO/IEC68.2.6 (10g, 10...2000 Hz)	(3 axis, 2,5 h)	
Mechanical:	Shock: ISO/IEC68,2,27 (100g, 6ms, 6 axis, 20 times per axis) Stability: Axial/Radial compr. 1000 N / 500 N (10 s static). Isostatic water pressure: 45 bar (10h)		
Reading Range:	Depending on the reader design	and local installation conditions.	
Specials:	64 bits UID code laser engraved as standard on housing.		
Number of washing Cycles:	200		
Part number:	TCE-26-AA	MPQ: 1000 pieces per bulk	

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.