

OBVIOS® Aegis



PRODUCT DESCRIPTION

Aegis LCD monitors are compact units encased in injection-molded die-cast aluminium, and attach to any PC equipment that provides a standard VGA port.

Available in either Touch or Non-Touch models, the Aegis is ideal for those wishing to use a standard PC CPU or other control device. Equipped with optional Magnetic Card Reader, ELO resistive touch panel and VFD customer display, the Aegis is ideal for any retail or hospitality application.

APPLICATIONS

POINT OF SALE

EFTPOS

RETAIL

HOSPITALITY

MANUFACTURING

121A/121TA SPECIFICATIONS

Construction	Die-cast Aluminium Casing
LCD Display	12.1" 800x600 TFT colour LCD, 180cd/m ² brightness.
Touch Panel	ELO 5-wire resistive touch screen
Wall Mount	VESA FPMPI 75mm mounting interface
Height	290mm with display upright
Width	315mm, 360mm with MCR
Base Depth	172mm
Base Width	198mm
Display Height	240mm
Display Tilt	90° (upright) to 180° (flat)
Compliance	CE, Class-B, TUV, FCC, UL, CSA
Weight	6.3kg

152A/152TA SPECIFICATIONS

Construction	Die-cast Aluminium Casing
LCD Display	15" 1024x768 TFT colour LCD, 250cd/m ² brightness.
Touch Panel	ELO 5-wire resistive touch screen
Wall Mount	VESA FPMPI 75mm mounting interface
Height	330mm with display upright
Width	360mm, 405mm with MCR
Base Depth	200mm
Base Width	200mm
Display Height	280mm
Display Tilt	90° (upright) to 180° (flat)
Compliance	CE, Class-B, TUV, FCC, UL, CSA
Weight	6.4kg

INTERFACE

121TA	VGA interface, 180 nits, with ELO touch panel. from standard VGA port
121A	VGA interface, 180 nits, with out touch panel. from standard VGA port
152TA	VGA interface, 250 nits, with ELO touch panel. from standard VGA port
152A	VGA interface, 250 nits, with out touch panel. from standard VGA port

OPTIONS

Customer 2 x 20 VFD display
Magnetic card reader
32 keys key pad