# **H 16A**

Smartphone







The H16A is a high-performance Quad-band smartphone with an integrated 1D scan engine, a slide-out QWERTY keyboard and multiple modes of wireless communication (GSM/GPRS/EDGE, WiFi and Bluetooth™) to meet the needs of your mobile workforce.

## Product Features

# **Convergence for Mobile Business**

The H16A delivers the convergence of a Windows Mobile™ based smartphone and Opticon's latest scan engine technology to allow for the seamless integration of barcode based data-capture into your mobile business.

## **Extending the Desktop beyond the Desk**

Microsoft Windows Mobile™ 5.0 drives the H16A and this mobile extension of the familiar desktop environment allows your mobile workers to be productive almost instantly. Your workforce will have on-demand access to well known applications as well as extensions of custom enterprise applications regardless of physical location.

## Ease of Use on Demand

The slide-out QWERTY keyboard provides fast and easy text input and quickly hides away when not required. The 2.8-inch, color touch-screen LCD includes the ability to instantly rotate the screen layout when your applications require increased screen space.

## Keep in touch wherever you are!

With Quad-band GSM/GPRS/EDGE, WiFi (802.11b/g) and Bluetooth™ support onboard, your workforce can easily connect to voice/data networks and peripheral devices for real-time remote data-capture, email and office productivity on the go, and other business applications that require network connectivity while away from the office.





#### **Electrical specifications**

Main battery pack: Rechargeable Lithium Ion Polymer 4.2 V 1440 mAh Main battery pack operating time: Talk time 4 hours, standby time 150 hours Battery charging time: 4 hours (full charge)

## Optical specifications

Light source: 650 nm visible laser diode

Scan rate: 100 scans/sec

Reading pitch angle: -35 to 0°, 0 to +35° Reading skew angle: -50 to -8°, +8 to +50° Reading tilt angle: -20 to 0°, 0 to +20° Curvature: R>15 mm (EAN8), R>20 mm (EAN13)

Min. resolution at PCS 0.9: 0.127 mm / 5 mil

Min. PCS value: 0.45

#### Communication specifications

Interface: Mini SDIO card slot, mini USB (client, ver 1.1)

Interface Bluetooth: Ver. 1.2

Interface W-LAN: WiFi, IEEE.802.11b/g

Interface GSM/GPRS: Quad-band 850/900/1800/1900, GSM Class 12, EDGE Class 10

#### Identification

Supported barcode symbologies (1D): JAN/UPC/EAN (WPC) incl. add on, JAN/ UPC/EAN (WPC) incl. add on, Chinese Post, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Korean Postal Authority code, Matrix 2of5, MSI/Plessey-UK/Plessey, RSS, S-Code, Telepen, Tri-Optic, Composite codes Supported 2D code symbologies: MicroPDF417, PDF417

## **Functionality**

Memory FlashROM: 128 MB Disc on Chip

Memory RAM: 64 MB RAM

Microprocessor: Samsung S3C2440A 400Mhz

Display: 2.8 in Transflective TFT LCD with backlight, 240 x 320 pixels, 16-bit color

Indicators: 2 LEDS (red/orange/green/blue), speaker, vibrate

Input devices: Touch panel with stylus, 41 keys QWERTY keyboard, virtual keyboard, handwriting recognition, 5-way direction keys, 2 scan buttons, hot keys, phone buttons

O/S: Windows Mobile™ 5.0

Programming: Pre-loaded software: Excel Mobile, Powerpoint Mobile, Word Mobile, Internet Explorer, ActiveSync, Internet sharing, Pocket MSN, Phone application, Opticon Scanner application, Accessories

## **Environmental specifications**

Temperature in operation: 0 to 45 °C / 32 to 113 °F Temperature in storage: -10 to 60 °C / 14 to 140 °F Humidity in operation: 20 - 80 % (non-condensing) Humidity in storage: 20 - 85 % (non-condensing)

## Physical specifications

Dimensions: 60 x 127 x 28 mm / 2.36 x 5.00 x 1.10 in Weight body: Ca. 180 g / 6.3 oz (excl. battery)

## Regulatory

Laser safety class: JIS-C-6802 Class 1, IEC 60825-1 Class 1, FDA CDRH Class I Product compliance: CE, FCC, VCCI, ROHS

## **Enclosed items**

AC adapter, Ear microphone, USB cable (client to host), Leather case, Lithium-Ion Polymer battery, Getting Started disc, Stylus

## Accessories

sold separately

Car charging adapter, Car mount holder, Headset

Copyright Opticon. All rights reserved. This information is subject to change without prior notice

- Taiwan: Taipei

- Australia: Kariong

B\_H16A\_001

- The Netherlands: Hoofddorp

- France: ISSY Les Moulineaux CEDEX - P.R.China: Shanghai

- Germany: Dietzenbach

- Italy: Castel Maggiore (BO) - Spain: Valencia

- Sweden: Järfälla

- United Kingdom: Luton, Bedfordshire - U.S.A.: Orangeburg, NY - Bellevue, WA

- Japan: Warabi City

Opticon Sensors Europe B.V. European headquarters Opaallaan 35 2132 XV Hoofddorp The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266

email: sales@opticon.com internet: www.opticon.com

