

The Revolutionary Printer

*Portable,
Handy
Smart*



▶ User-configurable Printer with AEP Technology

Powered by AEP (Application Enabled Printing) Printer Technology, use the TH2 to create any printer application without the need to modify printer firmware.

▶ AEP Software

- AEP Works™: Create custom label designs, manage data-base and files
- PSIM (Printer Simulator): Virtually preview printer operation, LCD menus and printed label layouts
- TH2 Downloader: Transfer files from PC to printer

▶ Standalone Printing Capability

- Built-in keypad, no need for PC

▶ High Resolution Printing

- Prints text, graphics, linear and 2D barcodes

▶ Anti-Microbial Casing

- Ideal for clean environments where hygiene control and contamination prevention is vital (E.g. Food preparation)

TH2

INDUSTRY VERTICALS

- Food Manufacturing (Preparation)
- Hospitality & Commercial Services
- Food Distribution & Services
- Retail

APPLICATIONS

- Price marking & price markdown
- Shelf labelling
- Food preparation labelling
- Parking Tickets/ Receipts
- Food safety labelling
- Ingredient labelling
- Small goods labelling (E.g. Cosmetics, jewellery)
- Stock control
- Item identification
- Incoming goods labelling

FEATURES

- Compact
- Portable, battery operated printer
- Real time calendar for date coded labelling
- Wide and adjustable LCD screen display
- Easy file transfer/ update of product lists
- Supports 2D barcode printing
- Multiple Interface – USB/ LAN
- Supports multiple language printing & display

ACCESSORIES



Cutter
Cuts and separates each label from another for easy application

PRINTER MODEL

TH2

PRINT SPECIFICATIONS

Print method	Direct thermal method
Print resolution	8 dots/mm (203dpi)
Max. print speed	100 mm/sec (4ips)
Max. print area	(WxP) 56mm x 156mm (2.2" x 6.14")
CPU	32bit RISC-CPU
Printer Body Memory	Main memory (Flash ROM): 12MB, 8 MB SDRAM

MEDIA SPECIFICATIONS

Sensor type	I-Mark Sensor, Label Gap Sensor		
Media	Label size	Continuous	L: 16 ~ 156mm (0.9" to 6.1"), With backing paper: 19 ~ 159mm (0.7" to 6.2") W: 25 ~ 60mm (0.9" to 2.3"), With backing paper: 28 ~ 63mm (1.1" to 2.4")
		Cutter	L: 16 ~ 156mm (0.6" to 6.1"), With backing paper: 19 ~ 159mm (0.7" to 6.2") W: 25 ~ 60mm (0.9" to 2.3"), With backing paper: 28 ~ 63mm (1.1" to 2.4")
		Tear-off	L: 16 ~ 156mm (0.6" to 6.1"), With backing paper: 19 ~ 159mm (0.7" to 6.2") W: 25 ~ 60mm (0.9" to 2.3"), With backing paper: 28 ~ 63mm (1.1" to 2.4")
		Dispenser	L: 16 ~ 117mm (0.6" to 4.6"), With backing paper: 16 ~ 120mm (0.6" to 4.7") W: 25 ~ 60mm (0.9" to 2.3"), With backing paper: 28 ~ 63mm (1.1" to 2.4")
		Linerless (w/o cutter)	L: 25.4 ~ 100mm (1" to 3.9"), W: 28 ~ 60mm (1.1" to 2.3")
		Linerless (with cutter)	L: 45 ~ 100mm (1.7" to 3.9"), W: 28 ~ 60mm (1.1" to 2.3")
	Label thickness		0.14 ~ 0.19mm (0.005" x 0.007")
	Wind Direction		Face-in/Face-out
	Media roll size		Max external diameter: 75mm (2.9"), Paper core internal diameter: 26mm (1.0")

FONT/SYMBOLOGIES

Standard fonts	Bitmap fonts	M 13×20, S 8×15, U+XU 5×9 (Alphanumeric, Symbols), X1 20×50(Alphanumeric, Symbols), X2 8×20(Alphanumeric, Symbols), X3 13×21(Alphanumeric, Symbols), OCR-B 20×24(Alphanumeric Capital), PRICE Character 16×24 (Number, Period, Currency Mark), POP1 28×48(Number, Currency Mark, Comma), POP2 48×68(Number, Currency Mark, Comma), POP3 26×56(Number, Currency Mark, Comma), Support subscript (e.g. the 2 in H ² O) (Numbers Only) X1, X2, X3
	Rasterized fonts	Sato Sans, Sato Serif
Barcode	1D barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128A/B/C, GS1-128 (UCC/EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2-5 char add-on code), GS1 Databar (RSS14)
	2D barcode	QR Code (Including Ver.8.1 Micro QR), Datamatrix
Print direction	Bitmap text and barcodes 0°, 90°, 180°, 270°. True Type text can be rotated at 1° increments	

COMMUNICATION INTERFACE

Interface	USB (Full speed) or USB + LAN
Command	Lua version 5.1 pre-loaded, Lua Standard API (SATO proprietary) version 1.0

OPERATING CHARACTERISTICS

Power requirements	AC adaptor	Input voltage AC100~240V±10%
Consumption voltage	At peak (30% printing ratio): 64.0VA/42.5W, standby: 12.6VA/6.2 W	
Environment	Operating	0~40°C/30~80% RH (without condensation)
	Storage	Storage Environment:-5~60°C/30-90% RH (without condensation)
Dimension	(WxDxH): 132 x 194 x 147mm (5.19" x 7.64" x 5.79")	
Weight	1.7 kg (3.78 lbs)	
OPTIONS	Cutter, Rewinder, Unwinder, Barcode scanner, Battery, Battery charger	

MISCELLANEOUS

Regulatory approvals	USA / Canada: FCC15B Class B, Europe: CE (EN55022, EN55024), Singapore: IDA. China: GB9254-1998 GB17625.1 (2003), Korea: KN22, KN24
Anti-bacterial finishing	Resin of the enclosure/ control panel includes an anti-bacterial substance tested according to JIS Z 2801: Product test for antimicrobial activity and efficacy.

Contact

 For a full list of all SATO offices, refer to www.satoworldwide.com

AMERICAS

SATO INTERNATIONAL AMERICA, INC.
 (Regional Sales HQ)
 P: +1 704 644 1650
 E: satosales@satoamerica.com
 W: www.satoamerica.com

SATO AMERICA, INC.

P: +1 704 644 1650
 E: satosales@satoamerica.com
 W: www.satoamerica.com

SATO LABELING SOLUTIONS AMERICA, INC.

P: +1 630 771 4200
 E: sales@satolabeling.com
 W: www.satolabeling.com

EUROPE

SATO INTERNATIONAL EUROPE N.V.
 (Regional Sales HQ)
 P: +32 (0)2 788 80 00
 E: info@be.satoeurope.com
 W: www.satoeurope.com

SATO UK LTD.

P: +44 (0) 1255 2400 00
 E: enquiries@satouk.com
 W: www.satouk.com

SATO LABELLING SOLUTIONS EUROPE GmbH

P: +49 6272 9201 324
 E: info@de.satoeurope.com
 W: www.satoeurope.com/de

SATO POLSKA SP. Z O.O.

P: +48 71 381 03 60
 E: info@pl.satoeurope.com
 W: www.satoeurope.com/pl

SATO FRANCE S.A.S.

P: +33 (0)3 20 62 96 40
 E: info@fr.satoeurope.com
 W: www.satoeurope.com/fr

SATO IBERIA S.A.U.

P: +34 902 333 341
 E: info@es.satoeurope.com
 W: www.satoeurope.com/es

ASIA PACIFIC AND OCEANIA

SATO INTERNATIONAL ASIA PACIFIC PTE. LTD.
 (Regional Sales HQ)
 P: +65 6271 5300
 E: sales@satoasiapacific.com
 W: www.satoworldwide.com

SATO ASIA PACIFIC PTE. LTD.

P: +65 6271 5300
 E: sales@satoasiapacific.com
 W: www.satoasiapacific.com

SATO AUTO-ID MALAYSIA SDN. BHD.

P: +60 3 7620 8901
 E: sales@satosms.com.my
 W: www.satoasiapacific.com

SATO AUTO-ID (THAILAND) CO., LTD.

P: +662 736 4460
 E: sales@satothailand.co.th
 W: www.satoasiapacific.com

SATO SHANGHAI CO., LTD.

P: +86 (021) 6306 8899
 E: sales@satochina.com
 W: www.satochina.com

SATO AUSTRALIA PTY LTD.

P: +61 3 8814 5330
 E: sales@satoaustralia.com
 W: www.satoaustralia.com

SATO NEW ZEALAND LTD.

P: +64 9 477 2222
 E: sales@satonewzealand.com
 W: www.satonewzealand.com