

APOS

SENIOR **APOS** is a high performance POS system specially designed to be suitable for a wide range of applications. This all-in-one unit incorporates Smart Battery as a standard feature providing both UPS for protection from bad power or power failure and safe shutdown to preserve the operating state of the system until power is restored. This special feature provides reliability and protects the Hard Disk with it's cleaner power.

- Infrared Touch / Five Wire Resistive Touch
- Adjustable Backlight Brightness
- Motorized Tilting Adjustment
- Internal Smart Battery
- Internal Wireless LAN
- Internal Smart Fan
- Splash Resistant
- VESA Mount

APOS 600 Exclusive

- **Smart Battery Management**

APOS 600 is capable to display the battery status as well as to remind you while the battery is low.

With all these advanced features, SENIOR **APOS** will provide the best POS solution for any environment.



SENIOR

APOS



Multi-function Identification Device

Magnetic Card Reader
Smart Card Reader
RFID
Fingerprint
iButton



Web cam




DVD ROM



7" LCD



VESA Mount



270 degree Swivel



Motorized Tilting Adjustment

The SENOR **APOS** design is based on more than 20 years of experience in the POS industry. All key components and features are designed by SENOR, with only the highest grade materials selected and utilized.

- Precise screen angle adjustment with the press of a button
- Splash proof and dust proof – engineered for the demanding POS environment
- Convenient wireless infra red keyboard which reduces cable clutter
- Easy software installation and service with a removable HDD
- Bright and easy to read 20character x 2 line internal VFD Customer Display
- Space saving VESA Mount
- Hardware specifications can be customized to suit your specific requirements
- Manufacturer's sparing level is kept to reduce obsolescence and provide efficient servicing
- Smart Battery Function
- Back Light Adjustment
- Smart Fan Function to save power and reduce noise and dust
- Internal Wireless LAN
- Options include integrated Customer Display Magnetic Card Reader, Smart Card Reader, RFID, Fingerprint Reader and iButton

SENIOR

SENIOR TECH PTY., LTD.

65 Weaver Street, Coopers Plains
QLD 4108, Australia

Tel: +61 7 3275 5888
Fax: +61 7 3275 5800

<http://www.senor.com.au>
e-mail: sales@senor.com.au

**SENIOR TECH CO., LTD.**

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com**APOS 600**

2009/07/07

Name	Specification	
Main Board	ST-578P	
CPU Supports	Intel Atom N270 1.6GHz, w/ 512KB Cache	
System Memory	Two SODIMM DDR2 socket / 1GB up to 2GB DDR2 533	
Display Function	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m ² or 350 cd/m ²	
Touch Screen	ELO or SENOR five-wire Resistive Touch / Infrared Touch	
Connectivity		
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11 b/g/n Wireless LAN (Option)
USB	4x External USB ports	
External Serial	4X RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer	
Internal Serial	COM 1 for VFD, COM2 for Touch Panel	
Parallel	1 x Mini Printer Port	
PS/2 KB	1 x Mini Din Jack	
Audio	1 X Earphone Jack For Line- out	
Mechanical & Environment		
Dimension (W X D X H)	380 X 218 X 354 mm	
Weight	N.W. 7.1Kgs	
Motorized Angel Adjustment	SENIOR Patent Design	
Smart Features	Internal Smart Battery, Internal Smart Fan	
Infrared Function	Built-in Infrared K/B & Mouse Receiver	
Splash Resistant	IP43	
Safety Certifications	FCC / CE / CCC / UL / CB	
Storage temperature	-20℃~60℃	
Operating temperature	0°~40℃	
Relative Humidity	20%-80% (non-condensing)	
Software		
Operation System	Windows 2000 / XP / CE(5.0) / Business Vista / Windows 7	
Self-testing program	Observer software	
Peripheral Options		
Infrared keyboard	Keyboard wedge interface	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
RFID	ISO/IEC 14443A / 13.56MHz	
Smart Card Reader	ISO-7816 compatible	
Finger Print Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Modem	56 Kbps Modem	
Customer Display	VFD 20x2 lines Display / LCD Graphic Display	

※**NOTE:** The product information and specifications are subject to change without notice.