

DUAL APOS

The SENOR APOS design is based on more than 20 years of experience in the POS industry. All key components and features are designed by with only the highest grade materials selected and utilized.

Hospitality • Retail • Harsh Environment

- Splash proof – engineered for the demanding POS environment
- Convenient wireless infra red keyboard
- Easy software installation with a removable HDD
- Manufacturer's sparing level is kept to reduce obsolescence and provide efficient servicing
- Smart Fan Function to save power and reduce noise and dust



DUAL APOS



- Smart Fan
- Smart Battery
- Back Light Adjustment
- Internal Wireless LAN
- **APOS** - 6 tilting angles, each angle is 6° apart from the other.
- **Second Display** - 4 tilting angles, each angle is 7° apart from the other.
- **4-in-1 Card Reader**
Magnetic Card Reader,
Smart Card Reader
RFID, Fingerprint Reader and
iButton



12" Second Display



15" Second Display



SE
NOR

SENIOR TECH PTY., LTD.

65 Weaver Street, Coopers Plains QLD 4108, Australia

<http://www.senior.com.au>

e-mail: sales@senior.com.au

TEL : +61 7 3275 5888

FAX : +61 7 3275 5800

**SENIOR TECH CO., LTD.**

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com**APOS 600**

2009/07/07

Name	Specification	
Main Board	ST-578P	
CPU Supports	Intel Atom N270 1.6GHz, w/ 512KB Cache	
System Memory	Two SODIMM DDR2 socket / 1GB up to 2GB DDR2 533	
Display Function	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m ² or 350 cd/m ²	
Touch Screen	ELO or SENOR five-wire Resistive Touch / Infrared Touch	
Connectivity		
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11 b/g/n Wireless LAN (Option)
USB	4x External USB ports	
External Serial	4X RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer	
Internal Serial	COM 1 for VFD, COM2 for Touch Panel	
Parallel	1 x Mini Printer Port	
PS/2 KB	1 x Mini Din Jack	
Audio	1 X Earphone Jack For Line- out	
Mechanical & Environment		
Dimension (W X D X H)	380 X 218 X 354 mm	
Weight	N.W. 7.1Kgs	
Motorized Angel Adjustment	SENIOR Patent Design	
Smart Features	Internal Smart Battery, Internal Smart Fan	
Infrared Function	Built-in Infrared K/B & Mouse Receiver	
Splash Resistant	IP43	
Safety Certifications	FCC / CE / CCC / UL / CB	
Storage temperature	-20℃~60℃	
Operating temperature	0°~40℃	
Relative Humidity	20%-80% (non-condensing)	
Software		
Operation System	Windows 2000 / XP / CE(5.0) / Business Vista / Windows 7	
Self-testing program	Observer software	
Peripheral Options		
Infrared keyboard	Keyboard wedge interface	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
RFID	ISO/IEC 14443A / 13.56MHz	
Smart Card Reader	ISO-7816 compatible	
Finger Print Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Modem	56 Kbps Modem	
Customer Display	VFD 20x2 lines Display / LCD Graphic Display	

※**NOTE:** The product information and specifications are subject to change without notice.