

iSPOS



Robust | Power | Precision



SENIOR

The ISPOS is a Mix of Contemporary Design and Great Functionality



Stay ahead of the competition with SENOR's fan-less touch system all-in-one, ISPOS. Enclosed in a heat dissipating solid aluminum die-cast casing, the ISPOS offers innovation and precision at it's finest.

The ISPOS has undergone stringent industrial testing to ensure qualifications received for 'Ingress Protection'. Awarded IP66 certification, the ISPOS ensures total protection against dust and strong jets of liquids from all directions.

Furthermore, the 30degrees angle tilt of the card reader provides user comfort and convenience. Designed with the natural movement of the human body in mind, the ISPOS is an ergonomic Touch Screen System.



SENIOR



DUAL ISPOS: Dual Results

The Dual ISPOS offers all the features of a Point of Sale terminal and much more. It engages the customer at the point of purchase through promotions, advertising and motion videos from the second display.

Dual ISPOS is not only versatile, but it also provides maximum eye-catching exposures to your customers.

The second screen can aid sales through attention grabbing interactive displays and influence the customers purchasing decision right at the point of purchase whilst at the same time offering live newsfeeds and weather forecast.

Achieve more with the DUAL ISPOS.




Various mounting ability for versatility and convenience

Providing **Superior** User Safety and Peace of Mind.

The Dual ISPOS provides enhanced security features such as concealed mounting hardware and internal cable management, along side an elegant design, giving your point-of-sale hardware a professional and state of the art finish.

Dual Screens, Dual Functionality, Dual Benefits





Warehouse. Hospitality. Retail. Bakery. Resort. Marine. Industrial. Medical
Quality. Safety. Versatility

The Senor Building
65 Weaver Street
Coopers Plains
QLD. Australia. 4108

P: +61 7 3275 5888

F: +61 7 3275 5800

sales@senortech.com.au
www.senortech.com.au



Global Offices
Taiwan | Australia | China | Netherlands | USA



iSPOS 650

2009/10/01

Name	Specification	
Main Board	GST-388	
CPU Supports	Intel Atom N270 1.6GHz, w/512KB Cache	
System Memory	2 x SO-DIMM DDR2 socket / 1GB up to 2GB DDR2 533	
Display Function	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 X 768	
Brightness	250 cd/m² or 350 cd/m²	
Touch Screen	ELO or SENOR Five-wire Resistive Touch	
Connectivity		
SATA/IDE	SATA: 1 X socket for HDD / 1 X Compact Flash Pocket	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11g Wireless LAN (Option)
USB	3 x External USB2.0 ports	
Parallel	1 x Mini Printer port	
External Serial	4 x RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer	
Internal Serial	COM 1 for VFD, COM2 for Touch Panel	
VGA / Printer Port	iSPOS 650 P (mini-printer port) / iSPOS 650 V (VGA port)	
PS/2 KB	1 x Mini Din Jack	
Audio	1 x Earphone Jack For Line-out	
Mechanical & Environment		
Dimension (W X D X H)	389 x 232 x 363 mm	
Weight	8.5 Kgs	
Fanless & Ventless	Aluminium Casing, Fanless & Ventless System	
Infrared Function	Built-in Infrared K/B & Mouse Receiver (Option)	
Splash Resistant	IP66 (IP43 with card reader)	
Safety Certifications	FCC / CE / CCC / TUV / CB	
Storage Temperature	-20°C ~ 60°C	
Operating Temperature	0° ~ 40°C	
Relative Humidity	20% ~ 90% (non-condensing)	
Software		
Operating System	Windows 2000 / XP / Business Vista	
Self-testing Program	SENR Self-testing software	
Peripheral Options		
Infrared Keyboard	Keyboard wedge Interface	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
Contactless Card Reader	RFID (ISO / IEC 14443A / 13.56MHz)	
Smart Card Reader	ISO-7816 Compatible	
Fingerprint Sensor	Optical Type, 512 dpi	
i-Button	Dallas Key	
Customer Display	VFD 20X2 lines Display / LCD Graphic Display	

* Note: The product information and specifications are subject to change without notice