

KDS 21

Kiosk Display System



IP66 Whole Unit



VESA Mount Capable*



Tool-free SSD Access



Internal Power Supply
Concealed Ports

* Mounting poles/brackets for VESA mount not included

SENIOR



SPECIFICATIONS

	KDS C3822	KDS X3220
PROCESSOR	Intel Celeron 3865U 1.8 GHz	Intel Core i3-7020U 2.3 GHz
SYSTEM MEMORY	1 x DDR4 SODIMM RAM (up to 16 GB)	
STORAGE	1 x removable SATAIII M.2 2280 SSD 1 x PCIe Gen3x4 M.2 SSD	

DISPLAY

SIZE	21.5" TFT LCD (LED backlight)
RESOLUTION	1920 x 1080 pixels
BRIGHTNESS	250 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	3 x USB 2.0, 1 x USB 3.0
SERIAL PORT	3 x RJ50
NETWORK PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (supports both 12 V & 24 V)
VIDEO PORT	1 x HDMI
AUDIO PORT	2 x 2 W speaker

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11
---------	----------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	519 (W) x 322 (H) x 46 (D) mm 8.0 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing
VESA PATTERN	100 x 100 mm
SAFETY CERTIFICATION & IP RATING	IP66 compliant
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	Relative: 10% to 90% (non-condensing)
POWER CONSUMPTION	DC output: 19 V / 5 A 65 W AC input: 100 V to 240 V

MODEL OPTIONS

INTEGRATED CARD READERS	MCR (Dual Head & Dual Directional)
WIRELESS LAN	Integrated Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.1

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.