

Pico POS900



Slim Base Design



Bezel-Less Design



Support VESA mount



IP64 Water & Dust Resistant for Front Bezel

SE/ATOR

Quality. Safety. Versatility

Technical specifications:

Display	LCD Display Size		15" TFT LCD
	Max. Resolution		1024 x 768
	Brightness		350 cd/m ²
Touch Panel	Type		5-wire Resistive Touch
Processor	CPU		Intel Celeron J1900 quad core 2.0GHz
Memory			4GB DDR3 (maximum up to 8GB RAM)
Storage			2.5" Removable SATA HDD/ SSD
Casing			Heat dissipating solid aluminium die-cast casing
I/O Connectors	USB		3x USB2.0, 1x USB3.0
	Powered COM		4x (Powered COM with DC 5V/12V)
	Cash Drawer Port		1x (12V RJ11 cash drawer port)
	Audio port	Speaker	2x
	VGA		1x
	Parallel		1x
Ingress Protection Standards			IP64 Water & Dust Resistant
Network	LAN		1x (RJ45 10/100/1000M)
Weight & Dimensions			373.8(W) x 340.1(H) x 267.5(D) mm, kg
Environment	Operation temperature		32° to 95° F (0° to 35° C)
	Storage temperature		-4° to 140° F (-20° to 60° C)
	Relative Humidity		20% to 80% non-condensing
Operating System			Windows POSReady7 / Windows 7 Pro/ 8.1 Pro/ 8.1 Industry Pro/ Linux
Optional Warranty			Extended Warranty and Onsite Warranty available upon request
Optional add-ons			VFD/ Second display/ MSR/ iButton/ Fingerprint reader/ Smart card reader/ 2D Barcode scanner

Technical specifications are subject to change without notice based on availability.



MSR & Finger Print Reader



Optional VFD



MSR 8" / 10.4" / 15"
Customer Display



2D Barcode Reader



Capacitive multi-touch



Inbuilt Wi-Fi

The Senor Building

65 & 67 Weaver Street
Coopers Plains QLD 4108
Brisbane, Australia
www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS