

cSMON



VESA Mount Capable



Cable Management Design



Integrated MSR* /
10" Customer Display*

* Optional configuration

SE/NOR



SPECIFICATIONS

DISPLAY SIZE	15" TFT LCD
RESOLUTION	1024 x 768 pixels
BRIGHTNESS	300 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (P-CAP)
TILTING ANGLE	15° to 85°

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	356 (W) x 303 (H) x 205 (D) mm 5 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing
VESA PATTERN	75 x 75 mm
TEMPERATURE	Operating: 5°C to 40°C Storage: -20°C to 60°C
HUMIDITY	Operating: 20% to 80% RH, non-condensing Storage: 20% to 85% RH, non-condensing
POWER CONSUMPTION	DC output: 12 V / 4.16 A 50 W (max.) AC input: 100 V to 240 V

MODEL OPTIONS

INTEGRATED CARD READER	Magnetic stripe card reader (USB)
CUSTOMER DISPLAY	10" TFT LCD (1024 x 768 pixels) display or 2-line VFD
COLOURED FRAME	Black (standard) / White (custom)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains QLD 4108
Brisbane, Australia

www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.