









## The ISPOS is a Mix of Contemporary Design and Great Functionality



Stay ahead of the competition with SENOR's fan-less touch system all-in-one, ISPOS. Enclosed in a heat dissipating solid aluminum die-cast casing, the ISPOS offers innovation and precision at it's finest.

The ISPOS has undergone stringent industrial testing to ensure qualifications received for 'Ingress Protection'. Awarded IP66 certification, the ISPOS ensures total protection against dust and strong jets of liquids from all directions.

Furthermore, the 30degrees angle tilt of the card reader provides user comfort and convenience. Designed with the natural movement of the human body in mind, the ISPOS is an ergonomic Touch Screen System.



















## **DUAL ISPOS: Dual Results**

The Dual ISPOS offers all the features of a Point of Sale terminal and much more. It engages the customer at the point of purchase through promotions, advertising and motion videos from the second display.

Dual ISPOS is not only versatile, but it also provides maximum eye-catching exposures to your customers.

The second screen can aid sales through attention grabbing interactive displays and influence the customers purchasing decision right at the point of purchase whilst at the same time offering live newsfeeds and weather forecast.

Achieve more with the DUAL ISPOS.



Various mounting ability for versatility and convenience

Providing Superior User Safety and Peace of Mind.





The Dual ISPOS provides enhanced security features such as concealed mounting hardware and internal cable management, along side an elegant design, giving your point-of -sale hardware a professional and state of the art finish.

## Dual Screens, Dual Functionality, Dual Benefits





Warehouse. Hospitality. Retail. Bakery. Resort. Marine. Industrial. Medical Quality. Safety. Versatility

The Senor Building 65 Weaver Street Coopers Plains QLD. Australia. 4108

P: +61 7 3275 5888 F: +61 7 3275 5800

sales@senortech.com.au www.senortech.com.au







## **iSPOS 670**

2010/04/02

	2010/04/02
Name	Specification
Main Board	GST-388
CPU Supports	Intel N270 1.6GHz, w/ 512KB Cache
System Memory	Two SODIMM DDR2 socket / 1GB up to 2GB DDR2 533
Display Function	Intel 945GSE Chipset
	Dynamic Video Memory up to 224MB shared with system
LCD Touch Panel	
LCD Size	17" TFT LCD
Resolution	1280 x 1024 pixels
Brightness	250 cd/m², 380 cd/m², 500 cd/m²
Touch Screen	ELO or SENOR five-wire Resistive Touch, SAW Touch, Capacitive Touch
Connectivity	
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket
LAN	1 x RJ-45 LAN port Internal 802.11g Wireless LAN (Option)
USB	10/100/1000 Mbps  3x External USB ports
External Serial	· · · · · · · · · · · · · · · · · · ·
	4X RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer
Internal Serial	COM 1 for VFD, COM2 for Touch Panel
Parallel	1 x Mini Printer Port
VGA / Printer Port	iSPOS 670 P (mini-printer port) / iSPOS 670 V (VGA port)
PS/2 KB	1 x Mini Din Jack
Audio	1 X Earphone Jack For Line- out
Mechanical & Environment	
Dimension (W X D X H)	446x246x420mm
Weight	9.6Kg
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System
Infrared Function	Built-in Infrared K/B & Mouse Receiver(Option)
Splash Resistant	IP66(IP43 with card reader)
Safety Certifications	FCC / CE / CCC / TUV / CB
Storage temperature	-20°C ~60°C
Operating temperature	-0°~40 ℃
Relative Humidity	20%-90% (non-condensing)
Software	
Operation System	Windows 2000 / XP / Business Vista
Self-testing program	SENOR self-testing software
Peripheral Options	
Infrared keyboard	Keyboard wedge interface
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks
Contactless Card Reader	RFID (ISO/IEC 14443A / 13.56MHz)
Smart Card Reader	ISO-7816 compatible
Finger Print Sensor	Optical Type, 512 dpi
I-button	Dallas Key
Customer Display	VFD 20x2 lines Display / LCD Graphic Display