

**SENIOR TECH CO., LTD.**

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com**iSPOS 650**

2009/10/07

Name	Specification	
Main Board	GST-388	
CPU Supports	Intel Atom N270 1.6GHz, w/ 512KB Cache	
System Memory	Two SODIMM DDR2 socket / 1GB up to 2GB DDR2 533	
Display Function	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m ² / 350 cd/m ²	
Touch Screen	ELO or SENOR five-wire Resistive Touch	
Connectivity		
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11g Wireless LAN (Option)
USB	3x External USB ports	
External Serial	4X RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer	
Internal Serial	COM 1 for VFD, COM2 for Touch Panel	
Parallel	1 x Mini Printer Port	
VGA / Printer Port	iSPOS 650 P (mini-printer port) / iSPOS 650 V (VGA port)	
PS/2 KB	1 x Mini Din Jack	
Audio	1 X Earphone Jack For Line- out	
Mechanical & Environment		
Dimension (W X D X H)	389 X 232 X 363 mm	
Weight	8.5 Kg	
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System	
Infrared Function	Built-in Infrared K/B & Mouse Receiver(Option)	
Splash Resistant	IP66(IP43 with card reader)	
Safety Certifications	FCC / CE / CCC / TUV / CB	
Storage temperature	-20℃~60℃	
Operating temperature	-0°~40 °C	
Relative Humidity	20%-90% (non-condensing)	
Software		
Operation System	Windows 2000 / XP / Business Vista	
Self-testing program	SENIOR self-testing software	
Peripheral Options		
Infrared keyboard	Keyboard wedge interface	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
Contactless Card Reader	RFID (ISO/IEC 14443A / 13.56MHz)	
Smart Card Reader	ISO-7816 compatible	
Finger Print Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Customer Display	VFD 20x2 lines Display / LCD Graphic Display	

※NOTE: The product information and specifications are subject to change without notice.