

# x5POS



reddot winner 2020



IP54 Whole Unit



Ultra-thin 10mm Panel



Wall Mount



VESA Mount

# SENIOR

## Modern. Elegant. Award-Winning Design.

The x5POS series represents a stylish space-saving system that is both portable and multi-functional.

The sleek base arm is sturdy yet easily adjustable to suit many functional positions.

### Easy peripherals installation

Plug and play accessories with modern USB ports.




### Ultra-thin bezel

On-cell PCT that provides seamless viewing experience.



- **Ergonomic dual hinge design** to suit most applications.
- **Foldable design** for **easy storage**.

## I/O Connector



### x5POS Standard Type

3 x USB | 2 x COM | 1 x Cash drawer port  
1 x LAN

## Optional Accessories



11.6" / 15.6" Customer Display  
with Accessories\*




VFD Customer Display



Wireless + Bluetooth



2D Barcode Reader



MSR Reader



Printer



RFID / Fingerprint Reader



## Mounting Options



VESA Mount



Wall Mount



Wall Mount with Printer

\* Customer display with accessories is by special order only.



| SPECIFICATIONS                          | x5C C38                                                               | x5C X35                     |
|-----------------------------------------|-----------------------------------------------------------------------|-----------------------------|
| PROCESSOR                               | Intel Celeron 3865U 1.8 GHz                                           | Intel Core i3-7020U 2.3 GHz |
| SYSTEM MEMORY                           | 4 GB DDR4 RAM                                                         | 4 GB DDR4 RAM               |
| STORAGE DEVICE                          | M.2 SATA SSD                                                          | M.2 SATA SSD                |
| DISPLAY                                 |                                                                       |                             |
| SIZE / RESOLUTION                       | 15.6" TFT LCD (LED backlight) / Full HD 1920 x 1080 pixels            |                             |
| BRIGHTNESS                              | 300 cd/m²                                                             |                             |
| TOUCH SCREEN PANEL                      | On-cell projected capacitive touch (10mm ultra-thin panel)            |                             |
| I/O INTERFACE                           |                                                                       |                             |
| USB PORT                                | 5 x USB 2.0, 1 x USB 3.0 (side)                                       |                             |
| SERIAL PORT                             | 2 x RJ50                                                              |                             |
| AUDIO PORT                              | 2 x built-in speakers / 2 x 2 W                                       |                             |
| CASH DRAWER                             | 1 x RJ12 (24 V)                                                       |                             |
| ETHERNET PORT                           | 1 x RJ45 10/100/1000 Mbps                                             |                             |
| OPERATING SYSTEM                        |                                                                       |                             |
| WINDOWS                                 | 10 IoT (64-bit) / 10 Pro (64-bit)                                     |                             |
| LINUX                                   | Kernel 3.0 up                                                         |                             |
| ENVIRONMENT & MECHANICAL SPECIFICATIONS |                                                                       |                             |
| DIMENSIONS & WEIGHT                     | 379 (W) x 232~431 (H) x 246 (D) mm   4.0 kg                           |                             |
| CHASSIS MATERIAL                        | Aluminium die-cast & Polycarbonate-ABS                                |                             |
| IP RATING                               | IP54 whole unit                                                       |                             |
| TEMPERATURE                             | Operating: 0°C to 40°C   Storage: -20°C to 60°C                       |                             |
| HUMIDITY                                | 10% to 90% (non-condensing)                                           |                             |
| POWER CONSUMPTION                       | 19 V / 3.15 A, external power adaptor, 100-240 V, 50/60 Hz            |                             |
| MODEL OPTIONS                           |                                                                       |                             |
| INTEGRATED READERS                      | 3-track MSR, Fingerprint reader, RFID (13.56 MHz), 2D image reader    |                             |
| CUSTOMER DISPLAY                        | 11.6" / 15.6" FHD LCD or 2-line VFD                                   |                             |
| WIRELESS LAN                            | Integrated Dual Band Wi-Fi 802.11 b/g/n/ac (2x2 MIMO) + Bluetooth 4.1 |                             |
| COLOURS                                 | Dark Grey (standard)   White (optional)                               |                             |

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## The Senor Building

65 & 67 Weaver Street  
Coopers Plains  
QLD 4108, Australia

[www.senortech.com.au](http://www.senortech.com.au)

P: +61 7 3275 5888  
[sales@senortech.com.au](mailto:sales@senortech.com.au)



**Quality. Safety. Versatility.**