



**SQUARE LABEL
32mm and 50mm
READ WRITE
ISO / IEC 15693
I-CODE SLI SL2**

Description:	SQUARE LABEL 32mmx32mm, 50mmx50mm I-CODE SLI SL2		
IC type:	Philips I-CODE SLI SL2 ICS20 1024 bits Read Write ISO 15693, ISO18000		
IC on request:	125 kHz: 5557, EM4100 Hitag series	13,56 MHz, Mifare series	
Physical:	Length x length:	32mmx32mm, 50mmx50mm	± 0.2 mm
	Thickness:	0.6 mm	± 0.02 mm
	Weight:	0.5 g	± 0.05 g
	Material:	Copper coil in paper	White
	Assembly	Sticker	
Electrical:	Operating Frequency:	13,56 MHz	+1 MHz – 0.5 MHz (At room temperature 20°C)
Thermal:	Operating Temperature:	-25°C to +50°C	
	Storage Temperature:	-25°C to 60°C	
Reading Range:	With TECTUS TID-470 CF Card Reader up to ca. 100 mm, Depending on the reader design and local installation conditions.		
Specials:	Printing of UID code, customised logos printing are available upon request.		
Size on request:	40mm x 40 mm	54mm x 86mm (Isocard size)	
Delivery form:	On roll		
Part numbers:	32x32mm: TBG-15-AA	50x50mm: TBH-15-AA	

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.