



TEAR KEYFOB HITAG 2

Description:	TEAR KEYFOB Hitag 2		
IC type:	Hitag 2 256 bit Read Write ASK		
IC on request:	(R/O EM4100, R/W 125 kHz: 5557, Hitag, other)	(R/W 13.56 MHz: I-CODE SLI SL2, Mifare)	
Physical:	Dimensions:	40 mm x 31 mm	
	Thickness:	4.8 mm	
	Hole Ø:	6 x 4 mm	
	Weight:	7 g	
	Material:	ABS	Black (other colours on request)
	Assembly:	Ultrasonic Welded	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz (At room temperature 20°C)
Thermal:	Operating Temperature:	-30°C to +65°C	
	Storage Temperature:	-35°C to +85°C	
Protection Class:	IP66 (20°C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Inkjet marking of UID code, customised logos are available upon request.		
Part number:	TBU-05-AA		

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.