



TEAR KEYFOB
MIFARE 1K
ISO-IEC14443A
ISO-IEC-18000-3

Description:	TEAR KEYFOB MIFARE 1K ISO-IEC14443A		
IC type:	NXP MIFARE S50 8096 bit Read Write, Anticollision, Cryptography		
IC on request:	(R/O EM4100, R/W 125 kHz: 5557, Hitag, other)	(R/W 13.56 MHz: I-CODE SLI SL2)	
Physical:	Dimensions:	40 mm x 31 mm	
	Thickness:	4.8 mm	
	Hole Ø:	6 x 4 mm	
	Weight:	7 g	
	Material:	ABS	Black with white inlay (other colours on request)
	Assembly:	Ultrasonic Welded	
Electrical:	Operating Frequency:	13,56 MHz	(At room temperature 20 °C)
Thermal:	Operating Temperature:	-30 °C to +65 °C	
	Storage Temperature:	-35 °C to +85 °C	
Protection Class:	IP66 (20 °C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions. With OEM Reader TLB-55 up to 80 mm.		
Specials:	Inkjet marking of UID code, customised logos, ATEX Version  are available upon request.		
	Produced under ISO9000: 2000 QS and  ATEX QS logistics controlled.		
Part number:	TBU-06-AA		