



TEC PLUG M30 134,2 kHz HDX

Description:	TEC PLUG M30 134,2 kHz HDX		
IC type:	HDX BDE Read Only FSK Modulation 134,2 kHz / 123,2 kHz		
IC on request:	134,2 kHz: FDX-B 5557 OTP, EM4100	ISO 11784 / 11785 BDE R/O,	13,56 MHz I-CODE SLI SL2
Physical:	Thread / Diameter:	M30 (mm)	± 0.5 mm
	Height:	15 mm	± 0.5 mm
	Holes:	4 (mounting tool available)	
	Weight:	11 g	± 0.5 g
	Material:	PA6 + PU	Black
	Assembly:	Shell filled with PU	
Electrical:	Operating Frequency:	134,2 kHz	(At room temperature 20 °C)
Thermal:	Operating Temperature:	-25 °C to +85 °C	
	Storage Temperature:	-25 °C to +85 °C	
Chemical:	Water Immersion IP67 (20 °C, 24 h, 1 m), Aqueous solution of salts,		
	Mineral and vegetable oil,	Petroleum, Unleaded gasoline	
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Customised logos are available upon request.		
Part number:	TAT-19-AA		

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.