

LP/TLP 2722,2742,TLP 3742 Specifications*

General Specifications	LP/TLP 2722	LP/TLP 2742	TLP 3742
Print Method (LP)	Direct Thermal	Direct Thermal	N/A
Print Method (TLP)	Direct Thermal/Thermal Transfer	Direct Thermal/Thermal Transfer	Direct Thermal/Thermal Transfer
Max. Print Speed	2 inches per second (51 mm/s)	2 inches per second (51 mm/s)	2 inches per second (51mm/s)
Dot Density	203 dpi (8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Memory (std./max.)	SRAM 128KB / 256KB FLASH 512KB / 1MB	SRAM 256KB / 512KB FLASH 512KB / 1MB	SRAM 512KB / 1MB FLASH 1MB
Media Width (min./max.)	1.12" (28mm) / 2.36" (60mm)	1.12" (28mm) / 4.65" (118mm)	1.12" (28mm) / 4.65" (118mm)
Media Diameter (max.)	5.0" (127mm) O.D.	5.0" (127mm) O.D.	5.0" (127mm) O.D.
Print Width (max.)	2.12" (54mm)	4.09" (104mm)	4.09" (104mm)
Print Length (min.)	0.38" (9.7mm)	0.38" (9.7mm)	0.38" (9.7mm)
(max. std.)	11" (279mm)	11" (279mm)	10" (254mm)
(max. opt.)	22" (561mm)	22" (561mm)	20" (508mm)
Ribbon Types (TLP only)	wax, wax/resin, resin	wax, wax/resin, resin	wax, wax/resin, resin
Ribbon Core Diameter	0.5" (12.5mm) I.D. core.	0.5" (12.5mm) I.D. core.	0.5" (12.5mm) I.D. core
Ribbon Widths	1.3" (33mm), 2.24" (56.9mm)	1.3" (33mm), 2.5" (64mm), 3.3" (84mm), 4.3" (109mm)	1.3" (33mm), 2.5" (64mm), 3.3" (84mm), 4.3" (109mm)
	Custom widths available on request	Custom widths available on request	Custom widths available on request
Ribbon Length	approx. 3600" (91m)	approx. 3600" (91m)	approx. 3600" (91m)
Graphic Features	Lines, boxes and graphics	Lines, boxes and graphics	Lines, boxes and graphics
Communications Interface	Centronics parallel or RS232C serial	Centronics parallel and RS232C serial	Centronics parallel and RS232C serial
Dimensions (W x D x H)	6.09" x 10.31" x 6.77" (155mm x 262mm x 172mm)	7.90" x 9.75" x 6.75" (200mm x 247mm x 171mm)	7.90" x 9.75" x 6.75" (200mm x 247mm x 171mm)
Printer Weight	2.87 lbs (1.3 Kg)	4 lbs (1.81 Kg)	4 lbs (1.81 Kg)
Shipping Weight	6 lbs (2.72 Kg)	7.5 lbs (3.40 Kg)	7.5 lbs (3.40 Kg)
Common Features			
Resident Bar Codes	• Code 39 • Extended Code 39 • Code 93 • Code 128 UCC • Code 128 Autoselect • Codabar • Interleaved 2 of 5 • UPC-A, UPC-E, 2 and 5 digit add-on • UPC Shipping container code • EAN-8, EAN-13, 2 and 5 digit add-on • UCC/EAN-128 • Postnet • German Postal Code • Maxi Code • PDF-417/Macro PDF • QR Code • Bar codes printed with or without human readable text • Bar codes can be printed in four directions: 0°, 90°, 180° and 270°		
Fonts	• International character sets • Five alpha-numeric fonts from .049" (1.25mm) to 0.23" (6.0mm) high • All fonts are expandable vertically and horizontally • Fonts can be printed in four directions: 0°, 90°, 180° and 270° • Smooth soft fonts can be downloaded from Eltron Font Downloader • All fonts can be printed in normal and reverse image		
Programming Language	• Eltron Programming Language 2 (EPL2)		
Software (included)	• Create-A-Label Tools and Windows™ Drivers		
Operating Temperature	• 40°F to 104°F (5°C to 40°C)		
Storage Temperature	• -40°F to 140°F (-40°C to 60°C)		
Humidity	• 10% to 90% non-condensing		
Electrical	• 2742/3742 - Nominal Voltage: 115V/230V, 60/50 Hz (Switcher) • 2722 - Nominal Voltage: Either 115V, 60 Hz or 230V, 50 Hz (Linear) • Complies with FCC Class A, CE, VCCI, C-Tick, UL, CUL, TUV		
Options and Accessories	• SRAM & FLASH Memory Expansion • Real Time Clock (time and date) • Label Present Sensor (peel mode) • Reflective Sensor for use with black marks • Cutter • Rewinder • Keyboard Display Unit (KDU) for stand-alone printing applications • RS422 interface • Asian character sets (Chinese, Japanese, Korean) available for 2722, 2742 • Battery Pack • Eltron PrintServer™ (LAN/Ethernet Adapter)		

Eltron®



*Specifications subject to change without notice. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. ©1999 Zebra Technologies Corporation. All Rights Reserved.

Corporate Headquarters

333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109 U.S.A
Telephone: +1 847 634 6700
Toll free in US: +1 877 462 9028
Fax: +1 847 913 8766

Other Locations

United States: California, Florida, Utah, Wisconsin
Europe: France, Germany, United Kingdom
Asia: Japan, Singapore

www.eltron.com