



UNIVERSAL KEYFOB BLUE
MIFARE 1K
13,56 MHz
ISO-IEC 14443A

Description:	UNIVERSAL KEYFOB BLUE MIFARE 1K		
IC type:	Mifare S50 8096 bits Read Write NXP (former Philips)		
IC on request:	(R/O 125 kHz EM4002, R/W 125 kHz: 5557, Hitag 1, 2, S)	(R/W 13.56 MHz: I-CODE SLI SL2, Mifare series)	
Physical:	Dimensions:	36.5 mm x 30 mm	± 0.5 mm
	Thickness:	7.5 mm	± 0.5 mm
	Hole:	4,2 mm x 8,4 mm	± 0.5 mm
	Weight:	5 g	± 0.3 g
	Material:	ABS	Standard Colour: Blue Pantone 661C
	Assembly:	Over moulded	(Black, Red, Green on request)
Electrical:	Operating Frequency:	13,56 MHz	(At room temperature 20°C)
Thermal:	Operating Temperature:	-20 °C to +75 °C	
	Storage Temperature:	-20 °C to +75 °C	
Protection Class:	IP66 (20 °C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions. With TECTUS OEM Board TLB-5x reader up to 80 mm		
Specials:	Laser engraving of UID code, customised logos (Inner circle for print or sticker Ø = 18,8 mm) are available upon request.		
Other:	Produced under ISO9000 QS conditions		
Part number	TBJ-06-AA		