




UNIVERSAL KEYFOB BLUE UNIQUE

Description:	UNIVERSAL KEYFOB BLUE Unique		
IC type:	EM4100 64 bit Read Only ASK Manchester		
IC on request:	(R/W 125 kHz: 5557, Hitag 1, 2, S)	(R/W 13.56 MHz: I-CODE SLI SL2, Mifare)	
Physical:	Dimensions:	36.5 mm x 30 mm	± 0.5 mm
	Thickness:	7.5 mm	± 0.5 mm
	Hole:	4,2 mm x 8,4 mm	± 0.5 mm
	Weight:	5 g	± 0.3 g
	Material:	ABS	Standard Colour: Blue Pantone 661C
	Assembly:	Over moulded	(Black, Red, Green on request)
Electrical:	Operating Frequency:	125 kHz	± 6 kHz (At room temperature 20°C)
Thermal:	Operating Temperature:	-20 °C to +75 °C	
	Storage Temperature:	-20 °C to +75 °C	
Protection Class:	IP66 (20 °C, 24 h, 1 m)		
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Laser engraving of UID code, customised logos (Inner circle for print or sticker Ø = 18,8 mm) are available upon request.		
Part number	TBJ-00-AA		

TECTUS declares that, in conformity with the Directive 2002/95/EC about the Restriction of Hazardous Substances (RoHS), this product is RoHS compliant.

The following substances: Cadmium and cadmium compounds, Lead and lead compounds, Mercury and mercury compounds, Hexavalent chromium compounds, Polybrominated biphenyls (PBB), Polybrominated Diphenylethers (BPDE) are not contained or if, in accordance with the limits required by the RoHS Directive.



Udo W. Doege

27. June 2006, Managing Director