



## WHITE DISC 20mm 25mm 30mm 5557

Description:	WHITE DISC 20mm 25mm 30mm 5557		
IC type:	ATA5557 RF/64 bit Read Write ASK Manchester		
IC on request:	125 kHz: EM4100, Hitag series	13,56 MHz: I-CODE SLISL2, Mifare series	
Physical:	Diameter:	20 mm, 25 mm, 30 mm	± 0.2 mm
	Thickness:	0.85 mm	± 0.05 mm
	Hole:	none	
	Weight:	1.0 g	± 0.5 g
	Material:	PVC	White
	Assembly	Laminated	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz (At room temperature 20 ℃)
Thermal:	Operating Temperature:	-25℃ to +50℃	
	Storage Temperature:	-25℃ to 60℃	
Reading Range:	Depending on the reader design and local installation conditions.		
Specials:	Printing or laser engraving of UID code, customised logos printing are available upon request.		
Part numbers:	Ø20mm: TBD-02-AA	Ø25mm: TBE-02-AA	Ø30mm: TBF-02-AA

<sup>©</sup> TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.