

Digital Scale Indicator with Check Weighing

Model : TSDI166SS

The TSDI166SS scale indicator features robust stainless steel housing suitable for use in wet environments and has an ingress protection rating of IP68. The stainless steel mounting bracket provides for optimal viewing of the easy to read large LCD which is backlit. NMI trade approved in Australia and data output is made easy via RS232C.

FEATURES

TSDI166SS

- NMI approved for trade use in Australia
- stainless steel housing with IP68 rating
- large (23mm high) easy to read, 6 digit display high contrast LCD, with backlight
- kg / lb conversion (available for non-trade use only)
- approved for connecting to up to 4 x 350Ω load cells
- zero point recall function(subject to local regulation)
- data output via RS-232C
- one touch high / ok / low function
- supplied complete with a stainless steel wall and desk bracket which allows the indicator to be set at the optimum viewing angle
- maximum display resolution of 15,000D (when not in trade use)

SPECIFICATIONS

Dimensions (mm): 220 (W) x 164 (H) x 83 (D)

OPTIONS

- optional capability for built in rechargeable battery



Specifications may change without notice.

Weighing Scales.

Labels. Packaging Equipment. Weighing Scales.
POS Systems. Food Equipment. Maintenance & Repairs. Hire.

Phone: 1300 970 111

enquiries@wedderburn.com.au

wedderburn.com.au

Stainless Steel Platform

Model : WS210SS Series

The WS210SS series platforms are designed to be used in wet environments. Featuring full stainless steel construction, stainless steel IP67 load cell, pole mounted or remote indicator and a number of capacities and sizes to choose from.

The platforms are designed to be paired up with our range of IP rated stainless steel indicators offering the ideal solution for your check weighing and portion control needs.

FEATURES

WS210SS SERIES

- full stainless steel construction
- pole mounted or remote mounted indicator
- IP67 stainless steel load cell
- NMI approved for trade use

SPECIFICATIONS

	WS210SS25306K	WS210SS253015K	W210SS253030K	WS210SS404030K	W210SS404060K
Capacity	6kg	15kg	30kg	30kg	60kg
Dimensions (mm)	250 (W) x 300 (D) x 107 (H)			400 (W) x 400 (D) x 118 (H)	

