



# ZEBRA DS4208

## GENERAL PURPOSE HANDHELD 2-D IMAGER

### 2-D BAR CODES — THE WAVE OF THE FUTURE IS HERE

2-D bar codes help businesses better manage inventory; cost-effectively comply with track and trace regulations for food, pharmaceuticals and more; and capture new types of data to improve overall process efficiency. In addition, both retailers and manufacturers alike must implement new standard 2-D bar codes that were created to streamline the entire supply chain. But 2-D imagers typically lack the speed and accuracy of 1-D laser scanners. How can you implement 2-D imaging without impacting business productivity?

### FUTURE-PROOF YOUR BUSINESS WITH HIGH PERFORMANCE AFFORDABLE 2-D IMAGING

The DS4208 delivers the blazing speed typical of laser scanners on both 1-D and 2-D bar codes, allowing you to accommodate 2-D bar codes without sacrificing scanning quality or performance. Users never need to take time to align the bar code with the scanner or pause between scans. And since you can capture bar codes printed on paper labels or displayed on the screen of a mobile phone, retailers can accommodate customers who download mobile coupons, mobile loyalty cards and more. You get industry leading scanning speed on every bar code; true point-and-shoot first time scanning simplicity on even damaged and poorly printed bar codes; and a durable design for all day everyday reliability — all at an affordable price.

### DRIVE CUSTOMER SERVICE AND REVENUE TO A NEW LEVEL WITH SUPPORT FOR MOBILE BAR CODES

Since the DS4208 can scan bar codes on mobile phone displays, you can attract the millions of customers who are using their cell phones to better manage their lives. Retailers can scan mobile coupons, mobile loyalty cards, mobile gift cards and more. Quick service restaurants can accept mobile coupons at the register. Location-based mobile couponing allows retailers and restaurants to entice customers to stop in by automatically issuing discount coupons when patrons are in the vicinity of your facility. Hotels can allow guests to use electronic loyalty cards stored on their cell phones, eliminating the need to carry physical cards. And since theaters, theme parks and stadiums can scan mobile tickets as easily as a paper ticket, they can offer customers an added convenience — paperless ticketing.

### GET THE SMART INVESTMENT WITH A LOW TOTAL COST OF OWNERSHIP (TCO)

The DS4208 is built to last — and our toughness tests prove it. The DS4208 delivers outstanding performance, even after exposure to heat, cold, dust, a spilled beverage — and 2,000 consecutive drops. In addition, with our unique support program, Service from the Start Advance Exchange Support, you can count on next-business-day device replacement — no questions asked — providing the uptime you need to keep business running smoothly. And with two Zebra tools — 123Scan<sup>2</sup> and Remote Scanner Management — everyday management is easier and less time consuming, reducing IT time and cost.

For more information on how the DS4208 can benefit your business, please visit us on the web at [www.zebra.com/ds4208](http://www.zebra.com/ds4208) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

### FEATURES

**Scans 1-D, 2-D and PDF417 bar codes on paper, mobile phones and computer displays**

Scan virtually any bar code on any medium; supports the technology your customers are embracing — electronic bar codes

**Two models to meet various data capture needs**

SR (Standard Range) designed for intensive scanning of paper and electronic (mobile phone) 1-D/2-D bar codes  
HD (High Density) for the tiny and dense codes common in manufacturing

**Omni-directional scan pattern**

Eliminates the need to align bar code and scanner

**Supports all common interfaces**

Easy integration with your existing technology environment; easily migrate to new hosts

**Rugged design: 6 ft./1.83 m drop to concrete**

Built to last, providing reliable operation despite spills and drops

**Compatible with 123Scan<sup>2</sup> and Remote Scanner Management (RSM)**

Reduces management time and cost, from initial configuration to day-to-day management

# SPECIFICATIONS CHART

## SYMBOLGY DECODE CAPABILITY

**1-D** UPC/EAN, UPC/EAN with supplementals, Bookland EAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, Chinese 2 of 5, GS1 DataBar variants, Korean 3 of 5, ISBT Concat

**2-D** PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec

**Postal** Australian Post, US PLANET, Royal Mail 4 State Customer, US POSTNET, KIX Code (Dutch), UK Postal, Japan Post, UPU 4 State Postal FICS (Post US4), USPS 4 State Postal (Post US3), Canadian Post (Postbar)

**Motion Tolerances** Up to 25 in. / 63.5 cm per second

**Interfaces Supported** The scanner supports the following protocols over USB: HID Keyboard (default mode), SNAPI, COM Port Emulation, IBM SurePOS (Yellowstone) (IBM Handheld, IBM Tabletop, OPOS); The scanner supports the following protocols over RS232: Standard, Wincor Nixdorf, ICL, Fujitsu, Olivetti, Keyboard Wedge and RS-485 IBM46xx

**Minimum Resolution** -SR: Code 39 4 mil; UPC 60% 5 mil; PDF417 5 mil, Datamatrix 7.5 mil  
-HD: Code 39 3 mil; UPC 60% 5 mil; PDF417 4 mil, Datamatrix 5 mil

## USER ENVIRONMENT

**Operating Temp.** 32° F to 104° F (0° C to 40° C)

**Storage Temp.** -40° F to 158° F (-40° C to 70° C)

**Humidity** 5% to 95%, non-condensing

**Drop Spec** Withstands multiple 6 ft. (1.83 m) drops to concrete

**Ambient Light Immunity** Immune to normal indoor lighting up to 1600 Lux. Immune to sunlight up to 86,000 Lux.

## PHYSICAL CHARACTERISTICS

**Dimensions** 6.7 in. H x 3.7 in. L x 2.7 in. W (17 cm H x 9.3 cm L x 6.8 cm W)

**Weight (w/o cable)** 6.1 oz. (172.9 g)

**Power** 5 VDC ± 10% @ 275 mA (RMS typical)

## PERFORMANCE CHARACTERISTICS

**Light Source** Aiming pattern: 617 nm LED  
Illumination: 625 nm LEDs

**Imager Field of View** 39° (H) x 25° (V)

**Roll** 0 - 360°

**Pitch** ± 65° or greater

**Yaw** ± 60° or greater

**Print Contrast** 25% minimum reflective difference

## ACCESSORIES

**Hands-Free Options** Gooseneck Intellistand

**Power Supplies** Power supplies are available for applications that do not supply power over the host cable

## REGULATORY

**Electrical Safety** UL60950-1 2nd ed, CSA C22.2 No . 60950-1 2nd ed, EN60950-1/ IEC60950-1 2nd ed.

**LED Safety** IEC/EN60825-1:2001, IEC/ EN62471:2006

**EMI/RFI** FCC Part 15 Class B, ICES-003 Class B, EN55022 Class B, EN55024

**Environmental** Compliant with RoHS directive 2002/95/EEC

## WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the DS4208 is warranted against defects in workmanship and materials for a period of 5 years from the date of shipment. For the complete Zebra hardware product warranty statement, go to: [www.zebra.com/warranty](http://www.zebra.com/warranty)

## RECOMMENDED SERVICES

**Support Services** Service from the Start Advance Exchange Support

# DECODE RANGES

SR Focus Range		Typical Working Ranges	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	0.2 in / 0.5 cm	6.8 in / 17.3 cm
80% UPCA	10.0 mil	0 in / 0 cm	12.7 in / 32.3 cm
100% UPCA	13.0 mil	0.3 in / 0.8 cm	15.2 in / 38.6 cm
PDF 417	5.0 mil	1.5 in / 3.8 cm	4.3 in / 10.9 cm
PDF 417	6.6 mil	0.8 in / 2.0 cm	6.0 in / 15.2 cm
Data Matrix	10.0 mil	0.4 in / 1.0 cm	7.2 in / 18.3 cm

HD Focus Range		Typical Working Ranges	
Bar Code Type	Symbol Density	Near	Far
Code 39	3.0 mil	0.2 in / 0.5 cm	3.7 in / 9.4 cm
Code 39	4.0 mil	0.1 in / 0.3 cm	4.6 in / 11.7 cm
Code 39	5.0 mil	0.1 in / 0.3 cm	5.1 in / 13.0 cm
Code 39	7.5 mil	0.1 in / 0.3 cm	6.4 in / 16.3 cm
Code 39	10.0 mil	0.2 in / 0.5 cm	7.7 in / 19.6 cm
60% UPC	7.8 mil	0.2 in / 0.5 cm	5.4 in / 13.7 cm
80% UPC	10.4 mil	0.3 in / 0.8 cm	6.5 in / 16.5 cm
100% UPC	13.0 mil	0.7 in / 1.8 cm	7.6 in / 19.3 cm
Code 128	5.0 mil	0.3 in / 0.8 cm	4.0 in / 10.2 cm
I2of5	10.0 mil	0.8 in / 2.0 cm	7.2 in / 18.3 cm
PDF 417	4.0 mil	0.7 in / 1.8 cm	2.7 in / 6.9 cm
PDF 417	5.0 mil	0.3 in / 0.8 cm	3.0 in / 7.6 cm
PDF 417	6.67 mil	0.4 in / 1.0 cm	3.6 in / 9.1 cm
PDF 417	10.0 mil	0.8 in / 2.0 cm	4.7 in / 11.9 cm
Data Matrix	5.0 mil	0.4 in / 1.0 cm	2.8 in / 7.1 cm
Data Matrix	7.5 mil	0.4 in / 1.0 cm	3.9 in / 9.9 cm
Data Matrix	10.0 mil	0.1 in / 0.3 cm	4.6 in / 11.6 cm
QR Code	10.0 mil	0.4 in / 1.0 cm	3.9 in / 9.9 cm



**ZEBRA**

Part number: SS-DS4208. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

---

**ZEBRA TECHNOLOGIES**