



MC45 MOBILE COMPUTER

ENTERPRISE VALUE WITHOUT COMPROMISE FOR FIELD MOBILITY

Improve customer service and workforce productivity out in the field with the affordable MC45. Your field workforce is your daily touchpoint with your customers. Whether they are repairing equipment, writing up sales or picking up and delivering shipments, how well they are enabled to perform their jobs directly impacts your revenue, customer satisfaction, customer retention and your growth potential. The MC45 is the affordable way to give your workers access to the real-time information needed to get the job done right, right on the spot preventing lost sales and lost customers. The MC45 gives you the right mix of features and enterprise rugged design in a compact device that fits in your budget. Workers get sleek styling and one-handed operation, along with the features, durability, security and manageability your business demands. So whether your workforce needs to access maintenance history for a repair, reserve product for a specific delivery date to close a sale, reconcile shipments, process returns or capture proof of delivery, theyll do it faster and more accurately with the MC45. The result? A field team that is more efficient, able to deliver the kind of service that leads to satisfied, loyal customers.

Class-leading ergonomics

Zebras award-winning Industrial Design team developed a pocketable device that is easy to hold, while key size, key placement and display size make it easy to see and easy to use.

True field durability

The MC45 is built for life out in the field, able to handle drops, bumps, spills, dust, vibration and the thermal shock that often occurs as workers travel from a climate controlled vehicle to the outdoors.

Advanced 1D scanning technology

BOOST EFFICIENCY AND CUSTOMER SERVICE IN:

Field sales

- Sales and pre-sales teams
- CRM
- Sales/order tracking
- Order taking
- Appointment scheduling
- Location-based services

Field service

- Technicians
- Service automation
- Inventory management
- Part inventory management
- Invoicing/signature capture
- Task management
- Order tracking
- Location based services
 - Appointment scheduling

DSD/Route accounting

- Pre-sales, delivery, vending, merchandiser, route drivers
- Automated ordering

Our industry-leading 1D scan engine with Adaptive ScanTM technology makes scan-intensive tasks easy a broad scanning range allows the easy capture of bar codes from near contact to as far as 15 ft./4.5 m away, even if they are dirty, damaged or poorly printed.

Inside-outside wireless connectivity

Keep workers connected out on the road and in the office with 3.5G GSM HSDPA cellular and 802.11a/b/g Wi-Fi.

GPS services in more areas

Workers can count on dependable GPS access to real-time directions and geostamps that automatically capture information for applications even in challenging urban areas, dense foliage or inside buildings.

Expand functionality with our complete accessory family

Our full family of desktop and vehicle charging cradles, holsters and cables makes it easy for users to manage the MC45 out on the road and in the depot. The MC45 can accept practically any type of payment including Chip and PIN-based credit and debit cards through Zebras Mobile Payment Module. Bluetooth provides an easy wireless connection to third-party mobile printers, headsets and more.

Comprehensive camera functionality

The integrated 3.2 MP color camera allows workers to capture practically any type of data to streamline business processes, including 2D bar codes, as well as photos and videos.

Best battery power in its class

With the most battery power in its class, the MC45 delivers plenty of power for a full shift even in wireless or usage intensive environments.

Built-in support for OS-agnostic applications

Support for Zebra Technologies RhoMobile Suite enables the deployment of HTML5 based OS-agnostic applications, substantially reducing application development time and costs a single application can run on mobile devices with different operating systems.

THE MC45 A NEW LEVEL OF AFFORDABILITY FOR FIELD MOBILITY

For more information, visit www.zebra.com/mc45 or access our global contact directory at www.zebra.com/contact

- Inventory reconciliation
- Delivery tracking
- · Full service vending,
- Direct Exchange/ Uniform Communication Standard (DEX)
- Competitive surveys
- Shelf space analysis
- Route optimization

Transportation & Logistics

- · Route drivers
- Pick-up and delivery
- Fleet management
- Proof of delivery
- Baggage and cargo tracking
- Dispatch and dynamic routing
- Stock keeping
- Signature capture
- Receiving and shipping
- Maintenance and repair facilities

SPECIFICATIONS CHART

| PHYSICAL CHARACTERISTICS | | DATA CAPTURE | |
|--------------------------|--|--|--|
| Dimensions | 5.6 in. L x 2.6 in. W x 1.0 in. D 14.2 cm L x 6.6 cm W x 2.5 cm D | Camera | Autofocus 3.2 MP with user-controllable flash; supports integrated 1D/2D bar code capture |
| Weight | 8.73 oz./247.4 g | 1-D Laser Scanner | 1-D* laser with Adaptive Scan technology |
| Display | Outdoor-viewable 3.2 in. QVGA with backlight, * Please refer to the lintegrator Guide for the l | | ne MC45 User Guide or or full data capture |
| Touchpanel | Polycarbonate analog resistive touch | specifications. | |
| Backlight | LE D backlight | WIRELESS WAN DATA AND VOICE - COMMUNICATIONS | |
| Standard Battery | Rechargeable Lithium Ion 3.7V, 3080 mAh | Radio | 3.5G HSDPA, Quad-Band GPRS/EDGE |
| Expansion Slot | User accessible 32 GB microSD slot with SDHC support | Frequency Band | GSM Quad Band : 850/900/ 1800/1900 MHz |
| Network Connections | USB 2.0 High Speed (host and client), WLAN, WWAN and Bluetooth | - | UMTS/HSDPA Americas: 850/1900 MHz UMTS/HSDPA Rest of the world: 2100 MHz |
| Notification | Vibrator and audible tone plus multi-color LED | GPS | Integrated, Autonomous and Assisted-GPS (A-GPS) |
| Keypad | 26-key numeric | | |
| Voice and Audio | VoWWAN: handset mode with active noise reduction, high-quality speaker phone, Bluetooth wireless headset mode | WIRELESS LAN DATA AND VOICE COMMUNICATIONS | |
| | | Radio | Tri-mode IEEE ® 802.11a/b/ g |
| | | Data Rates - Supported | 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps |
| PERFORMANCE | CHARACTERISTICS | Security | WPA2, WEP (40 or 128 bit), TKIP, TLS, TTLS (MSCHAP), TTLS (MS-CHAP v2), TTLS (CHAP), TTLSMD5, TTLS-PAP, PEAP-TLS, PEAP (MS-CHAP v2), AES, LEAP, CCXv4 certified |
| CPU | 600 MHz, ARM 11 processor , MSM 7627 | Geounty | |
| Operating System | Microsoft® Windows Embedded Handheld™ 6.5.3 Professional Edition | - | |
| Memory | 256 MB RAM / 1GB Flash | - | |
| USER ENVIRONMENT | | WIRELESS PAN DATA AND VOICE | |
| Operating Temp. | -10°C to 50°C/14°F to 122°F | COMMUNICATIONS | |
| Storage Temp. | -40°C to 70°C /-40°F to 158° F | Bluetooth | Class II , V2.0 with Enhanced Data Rate (EDR) |
| Humidity | 5% to 95% non-condensing | PERIPHERALS AND ACCESSORIES | |
| Drop Specification | Multiple 6 ft./1.8 m drops per MIL-STD-810G | Wall charger; Micro USB cables; single-slot charging cradle; 4-slot battery charger; | |
| Tumble | 250 0.5 m (1.5 ft.) tumbles (| innovative multi-slot cradle that holds term | |

| Specification | 500 drops); per applicable IEC tumble specifications | as well as battery charger through field replaceable cups; vehicle cradle with suction cup; auto charger; rugged USB adapter; DEX cable; holster and more. Visit www.zebra.com/mc45 for a complete list of accessories. | |
|--|---|---|--|
| ESD | +/-15kVdc air discharge, +/- 8kVdc direct discharge, +/-8kVdc indirect | | |
| | discharge | REGULATORY | |
| Sealing | IP 64 per applicable IE C sealing specifications | Visit www.zebra.com/mc45 for regulatory information | |
| Vibration | .02g2/Hz Random, Non-Operating, 1 hour duration per axis | | |
| | | WARRANTY | |
| Thermal Shock | -40°F to 158°F/-40°C to 70°C rapid transition | Subject to the terms of Zebras hardware warranty statement, the MC45 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of | |
| ZEBRA INTERACTIVE SENSOR TECHNOLOGY (IST) | | shipment. For complete warranty statement, go to: http://www.zebra.com/ | |
| Ambient Light Sensor | Automatically adjusts required display backlight | - warranty | |
| | to maximize power efficiency | RECOMMENDED SERVICES | |
| Proximity sensor | Automatically detects when the user places the handset against head during a phone call to disable display output and touch input | Managed Device Service. Outsource everyday device management to Zebra. We will track, monitor and manage your MC45 devices. | |
| | | Service from the Start with Comprehensive Coverage: A unique service that covers normal wear and tear as well as accidental damage to internal and external components. | |

Education galicy in productions





Part number: SS-MC45. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.



MC45

Configuration and Accessory Guide





MC45 Series





What is included in the box:







MC45 + Battery + Stylus

- + Quick Start Guide
- + Regulatory Guide
- + 1 Year Standard Warranty

Find Product Information in the **EMC Product Portfolio** on <u>The Source</u> and <u>PartnerCentral</u>



CONFIGURATION & ACCESSORY GUIDES are available on The Source and PartnerCentral

For access to additional product information including this guide, please visit: www.zebra.com/mc45



Step 1: Choose an MC45 configuration

| | | | , |
|------------------------|-------------------------|--------|-------------------------------------|
| CONFIGURATION OPTIONS: | MC45XX-XXXXXXX | OPTION | DESCRIPTION |
| | MC458x-xxxxxxx | 8 | No Wifi, BT 2.0, GPS |
| Radio | MC459x-xxxxxxx | 9 | 802.11 a/b/g, BT 2.0, GPS |
| | MC45Nx-xxxxxxx | N | No Wifi, BT 2.0, GPS, NFC (EA only) |
| MAN Confin | MC45xx-Axxxxxx | А | 2100 MHz HSDPA, Quad-band GSM |
| WAN Config | MC45xx-Bxxxxxx | В | 850/1900 MHz HSDPA, Quad-band GSM |
| Data Cantura | MC45xx-xAxxxxx | Α | SE965 + 3.2MP Camera |
| Data Capture | MC45xx-xBxxxxx | В | 3.2 MP Camera |
| | MC45xx-xxxxAxx | Α | English |
| | MC45xx-xxxxCxx | С | Traditional Chinese |
| | MC45xx-xxxxFxx | F | French |
| | MC45xx-xxxxGxx | G | German |
| Languago | MC45xx-xxxxlxx | I | Italian |
| Language | MC45xx-xxxxMxx | M | Simplified Chinese |
| | MC45xx-xxxxSxx | S | Spanish |
| | MC45xx-xxxx K xx | K | Korean |
| | MC45xx-xxxxJxx | J | Japanese |
| | MC45xx-xxxxPxx | Р | Brazilian Portuguese |

All currently available MC45 configurations include the following features:

- 1. WAN: GSM/HSDPA
- 2. Form Factor: PDA
- 3. Operating System: WEH 6.x Prof
- Memory: 256MB/1GB



Step 2: Choose a spare battery and spare battery charger







MC45 4-Slot Battery Charger requires a separate order of power supply (PWRS-14000-148C) and country specific 3 wire AC line cord sold separately



Step 3: Choose a charging method





Power Supply
PWRS-124306-01R

USB Cable 25-128458-01R

MC45 single slot cradle requires a separate order of power supply (PWRS-124306-01R) and USB Cable (25-MCXUSB-01R) sold separately





Power Supply PWRS-14000-148R

MC45 4 Slot Battery Chargers require a separate order of power supply (PWRS-14000-148R) and country specific 3 wire AC line cord sold separately



Step 4: Choose an auto charging method

Vehicle Charge Cradle



VCD45XX-1000R

Vehicle Charge Cradle for MC45; Passes Power to MC45 through bottom IO connectors. Includes Suction Cup Mount.



Must order Power Supply VCA400-01 separately

Vehicle Cradle Power Supply



VCA400-01R

12/24 VOLT MICRO USB AUTO CHARGER (Input: 12-24VDC 1.3A; Output: 5.0V—- 1.2A)

Note: the VCA400-01R is designed to connect directly to the micro USB on the vehicle cradle & should NOT be connected directly to your mobile computer.



Step 5: Choose cradle accessories

Cradle Base



CRDUNIV-XX-5000R

5 Slot Charge Only Cradle. Base only. Can accommodate up to 5 Cups.





CUPMC45XX-1000R

MC45 Replacement Charging Cup for 5 slot Charge Only Cradle – (QTY-1).

Note: Base, Power Supply, AC Line Cord all sold separately.

Cradle Parts



CUPUNIBTRY-1000R

4-Slot Battery Charger Adapter Cup. Provides ability to mount a 4-Slot Battery Charger on to the 5-Slot Charge Only Cradle (sold separately). 4-Slot Battery Charger requires its own power supplies.

Base and Powers Sold Separately.
See Cradle Configuration slide for more information.



CUPUNICVR-5000R

Blank Slot Covers for MC45 5-Slot Cradle - Plastic lid to cover and protect cradle charge slots when MC45 charge cups are not in use. (QTY-5).

Base and Powers Sold Separately. See Cradle Configuration slide for more information.



Step 6: Cradle configurations







Step 6: Cradle configurations

5-Slot Cradle & 4-Slot Battery Charger Power Supplies



PWRS-14000-148C

Power Supply 100-240VAC,12VDC,4.16A MOD. Order country specific three wire grounded AC Line Cord. See last page for AC Line cord List.

Single Slot Cradle Power Supply



PWRS-124306-01R

Power Supply 100-240 VAC, 5 V, 1.2 A with country specific plugs. Requires USB Cable (25-128458-01R)



Step 7: Choose USB accessories

Micro USB Adapter



◆ ADP45XX-100R

- Designed to allow rugged USB connections
- Easily replaceable
- •Supports DEX and other attached peripherals (Sold Separately



DEX Cable 25-45793-01R MC45 DEX Cable; Requires Adapter sold separately













Step 8: Choose soft goods











Step 9: Choose third-party accessories

Industrial Grade

ATP Industrial Grade microSD flash memory card designed and tested for rugged mobile computing and intensive program/erase operation.

Commercial Grade

Designed for READ intensive applications w/ STD data retention. For Read/Write intensive application that require extended data retention or harsh environments use SLC industrial grade

| Size | Pack | Industrial Grade | Commercial Grade |
|------|---------|------------------|------------------|
| 1GB | 1 Pack | AF1GUDI-MOT1-1P | |
| IGB | 10 Pack | AF1GUDI-MOT1-10P | |
| 2GB | 1 Pack | AF2GUDI-MOT1-1P | |
| ZGB | 10 Pack | AF2GUDI-MOT1-10P | |
| 4GB | 1 Pack | AF4GUDI-MOT1-1P | AF4GUD-MOT001 |
| | 10 Pack | AF4GUDI-MOT1-10P | |
| 9CP | 1 Pack | AF8GUDI-MOT1-1P | AF8GUD-MOT001 |
| 8GB | 10 Pack | AF8GUDI-MOT1-10P | |
| 16GB | 1 Pack | | AF16GUD-MOT001 |
| 32GB | 1 Pack | | AF32GUD-MOT001 |



Step 10: Choose country-specific AC line cord

| Country | Three Wire Grounded AC Line Cord |
|-----------|---|
| Abu Dhabi | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Australia | 50-16000-217R: 1.9M long, AS 3112 plug. |
| Bolivia | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Brazil | 50-16000-727R: 18AWG, 250V, 16A, BR (3w). |
| China | 50-16000-217R: 1.9M long, AS 3112 plug. 50-16000-257R: 1.8M long, IEC 60320 C13 plug. |
| Dubai | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Egypt | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Europe | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Hong Kong | 50-16000-219R: 1.8M long, BS1363 plug. |
| India | 50-16000-669R: 1.9M long, BS 546 plug. |
| Iran | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Iraq | 50-16000-219R: 1.8M long, BS1363 plug. |

| Country | Three Wire Grounded AC Line Cord |
|---------------|--|
| Israel | 50-16000-672R: 1.9M long, S132 plug. |
| Italy | 50-16000-671R: 1.8M long, CIE 23-16 plug. |
| Japan | 50-16000-218R: 1.8M long, NEMA 1-15P plug. |
| Korea | 50-16000-220R: 1.8M long, CEE 7/7 plug. 50-16000-256R: 1.8M long, CEE7/7 plug. |
| Malaysia | 50-16000-219R: 1.8M long, BS1363 plug. |
| New Guinea | 50-16000-217R: 1.9M long, AS 3112 plug. |
| Russia | 50-16000-220R: 1.8M long, CEE 7/7 plug. |
| Singapore | 50-16000-219R: 1.8M long, BS1363 plug. |
| UK | 50-16000-219R: 1.8M long, BS1363 plug. |
| US | 23844-00-00R: 7.5 feet long. 50-16000-221R: 1.8M long, USA NEMA 5-15P. |
| Vietnam | 50-16000-220R: 1.8M long, CEE 7/7 plug. |