

POWER SHIELD

Office

500 VA Powerboard UPS



Power  Shield™

UPS YOUR PRODUCTIVITY BY REDUCING YOUR DOWN TIME

POWER SHIELD

Office

		PSO500
Physical	Dimensions (DxWxH)	310x175x95mm / 12.2"x6.8"x3.7"
	Net Weight	5.1kg/11.2lb
Capacity	Total Capacity	1000VA
	Battery Backup	500VA/250W
Input	Voltage	230VAC
	Voltage Range	172~288Vac
	Frequency Range	50/60Hz +/- 10Hz
Output	Voltage	230VAC
	Voltage Regulation	+10~-15%, +/-10% Battery mode
Transfer Time		< 4mS (Typical)
Indicator	Flourescent	Turns on during power outage for emergency illumination
Audible alarm	Buzzer	Beeps during power outage
Protection	Tel/modem	Continuous, 1 in/2 out
	EFI, RFI	Continuous
	Coaxial	Optional
Environment		0-40°C, <90% humidity
Noise level		<45dB
Interface	RS232	Supports Windows 95/98/2000/NT/XP

* Specifications are subject to change without prior notice.

Power Shield Office Series Offers

- **Voltage Regulation**
AVR Buck and Boost Line Interactive design.
- **Data Line Protection**
1 in/2 out.
- **Power Strip Design**
Australian outlets allows additional power protection for office peripherals.
- **Smart Power Management**
Monitoring software included.

Features

- Light-weight, compact and elegantly designed
- Intelligent microprocessor control
- Monitoring and shutdown software included
- Fax/modem surge suppression port
- Overload protection and alarm
- Output short circuit protection
- Automatic Voltage Regulation (Buck and Boost)
- Start on battery function (cold start)
- Line-interactive design provides high reliability and efficiency
- Site-wiring-fault indicator
- Easy battery replacement mechanism
- USB option available
- Co-axial Surge suppression option available
- Extra Power Surge suppression module available



1679